

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 36; & 31 of T23-6

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 376 survey dated Jan. 22, 1881 (DCSO records Vol. 6 Page(s) 2391)

Set Cedar post for ¼ sec. cor., from which
A Fir 20" dia., bears N.40°E., 84 lks.
A Fir 20" dia., bears S.57°E., 46 lks.

BLM resurvey by Otis Gould, Joseph Gawron, and Orville Eggen, Cadastral Surveyors, under Group #244, surveyed June 1943/October 1957 (DCSO records Vol. 30 Page(s) 12650)

Point for the ¼ sec. cor. of secs. 31 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30" long, 2" dia., 18" in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd:
T23S
¼
R7W R6W
S36 S31
1957

from which
A Hemlock 17" dia., bears N.51°E., 24 lks. dist., mkd. ¼ S31 BT.
A Fir 17" dia., bears N.29½°W., 13 lks. dist., mkd. ¼ S36 BT.

BLM resurvey by Floyd A. Brooks, Cadastral Surveyor, under Group #244, Surveyed April/May 1964 (DCSO records Vol. 32 Page(s) 13498)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

From this point, the ¼ sec. cor., erroneously reestablished by Eggen in 1957, bears S.20°12'W., 0.44 chs. dist., set, marked and witnessed as described in the official record. I remove the iron post, destroy the marks on the bearing trees, and at the corner point

Reset the iron post, 28" long, 2½" dia., 24" in the ground with brass cap mkd:
T 23 S
R 7 W R 6 W
¼
S 36 S 31
1957

from which new bearing trees
(Cont. Next Page)

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 36; & 31 of T23-6

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

A Hemlock 14" dia., bears N.41 3/4°E., 16½ lks. dist., mkd. ¼ S31 BT.
A Hemlock 8" dia., bears S.70°W., 19 lks. dist., mkd. ¼ S36 BT.

BLM Corrective Dependent Resurvey by Wayne L. Rogers; Boyd W. Peterson; Philip G. Griffin; Dale T. Bedell; Cadastral Surveyors; and Robert H. Browning, Surveying Technician - under Group #'s 1266, 1637 and 1688, - surveyed June 9, 1986/August 22, 1995 - (DCSO records Vol. 51 Page(s) 19463-64)

The ¼ sec. cor., determined from the remains of the original bearing trees:

A fir stump, 40 ins. diam., bears N. 40° E., 84 lks. dist. (to the blaze), with scribe marks BT visible through a hollow center.

A fir stump, 42 ins. diam., bears S. 57° W., 46 lks. dist. (to the blaze), with scribe mark S visible on partially opened blaze.

From this point, the ¼ sec. cor. of secs. 31 and 36 erroneously reestablished by Brooks in 1964, bears S. 55° 23' 00" W., 1.325 chs. dist., monumented with an iron post, 2½ ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap marked and witnessed as described in the official record, except the NE. bearing tree is a stump. Remove the iron post, obliterate the marks on the stump, and at the true corner point:

Reset the iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T23S
R7W R6W
¼
S36 S31
1993

from which a bearing tree mkd. by Brooks

A hemlock, 13 ins. diam., bears S. 61½° W., 144 lks. dist., with healed blaze.

The corner is located in a clearcut logging area with no other suitable bearing trees available.