

TOWNSHIP 23 RANGE 07 POINT IDENTIFIER # 700200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25 & 36; 30 & 31, T23-6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 376 survey dated Jan. 22, 1861 (DCSO records Vol. 6 Page(s) 2391)

Set Chinkipin post for cor. secs. 25, 30, 31 and 36, from which

- A Fir 5" dia., bears N.80°E., 35 lks.
- A Cedar 12" dia., bears S.58°E., 70 lks.
- A Fir 36" dia., bears S.62°W., 29 lks.
- A Cedar 12" dia., bears N.21°W., 62 lks.

BLM resurvey by Otis Gould, Joseph Gawron, and Orville Eggen, Cadastral Surveyors, under Group #244, surveyed June 1943/October 1957 (DCSO records Vol. 30 Page(s) 12650-51)

Point for the cor. of secs. 25, 30, 31 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 2" dia., 24" in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd:

T23S
R7W | R6W
S25 | S30
S36 | S31
1957

from which

- A Fir 13" dia., bears N.85°E., 20 lks. dist., mkd. T23S R6W S30 BT.
- A Fir 8" dia., bears S.2°E., 42 lks. dist., mkd. T23S R6W S31 BT.
- A Fir 13" dia., bears S.20½°W., 52 lks. dist., mkd. T23S R7W S36 BT.
- A Cedar 8" dia., bears N.32°W., 10 lks. dist., mkd. T23S R7W S25 BT.

BLM resurvey by Floyd A. Brooks, Cadastral Surveyor, under Group #244, Surveyed April/May 1964 (DCSO records Vol. 32 Page(s) 13499)

The cor. of secs. 25, 30, 31 and 36, determined at record bearing and distance from the original bearing trees:

- A down Fir 26" dia., bears N.80°E., 35 lks. dist., with fragmentary scribe marks visible on opened blaze.
 - A down and decayed Cedar 20" dia., bears S.58°E., 70 lks. dist., with no marks remaining.
 - The stump hole of a Fir bears S.62°W., 29 lks. dist.
 - A down Cedar 32" dia., bears N.21°W., 62 lks. dist. with a healed blaze.
- (Cont. Next Page)

TOWNSHIP 23 RANGE 07 POINT IDENTIFIER # 700200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25 & 36; 30 & 31, T23-6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

From this point, the sec. cor. erroneously reestablished by Eggen in 1957, bears S.29°W., 0.63 chs. dist., set, marked, and witnessed as described in the official record. I remove the iron post, destroy the marks on the bearing trees, and at the original corner point:

Reset the iron post, 36" long, 2" dia., 24" in the ground, to bedrock, with brass cap mkd:

T	23	S
R	7	W
S	25	S
S	36	S
	1957	

from which new bearing trees

A Fir 14" dia., bears N.73½°E., 78 lks. dist., mkd. T23S
R6W S30 BT.

A Fir 7" dia., bears S.33½°E., 44 lks. dist., mkd. T23S
R6W S31 BT.

A Cedar 14" dia., bears S.37°W., 85 lks. dist., mkd. T23S
R7W S36 BT.

A Cedar 23" dia., bears N.12°W., 17 lks. dist., mkd. T23S
R7W S25 BT.

Fd. and Used in BLM Corrective Dependent Resurvey by Wayne L. Rogers; Boyd W. Peterson; Philip G. Griffin; Dale T. Bedell; Cadastral Surveyors; and Robert H. Browning, Surveying Technician - under Group #'s 1266, 1637 and 1688, - surveyed June 9, 1986/August 22, 1995 - (DCSO records Vol. 51 Page(s) 19464-65)

FD. Ok by D. Edwards, May 2005 - M147-56

Ron Rice - Josh Reed - 7/8/2010 - C.S. File 65/69-41

Condition report only

Found - 3¼" BLM brass cap dated 1957 with the following accessories:

41" W. Red Cedar bears N.12°W., 11.2' - healed face.

26" D.Fir bears N.73½°E., 51.5' - healed face.

24" W. Red Cedar bears S.37°W., 56.1' - healed face.

16" D.Fir bears S.33½°E., 29.0' - healed face.

Note - Corner has steel post adjacent to it. All BTs have red painted bands & yellow tags.