

TOWNSHIP 23 RANGE 07 POINT IDENTIFIER # 700340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 24; & 19 of T23-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 376 survey dated Jan. 22, 1881 (DCSO records Vol. 6 Page(s) 2392)

-----  
Set Cedar post for ¼ sec. cor., from which  
A Cedar 20" dia., bears N.25°E., 52 lks.  
A Cedar 24" dia., bears S.36°W., 22 lks.

BLM resurvey by Otis Gould, Joseph Gawron, and Orville Eggen, Cadastral Surveyors, under Group #244, surveyed June 1943/October 1957 (DCSO records Vol. 30 Page(s) 12652-53)

-----  
The ¼ sec. cor. of secs. 19 and 24, determined at record bearing and distance from an original bearing tree:

A Cedar 36" dia., bears N.25°E., 52 lks. dist., mkd. BT on exposed face.

At the corner point

Set an iron post, 3 ft. long, 2" dia., 18" in the ground, and in a mound of stone, 4 ft. base, to top, with brass cap mkd:

T23S  
¼  
R7W R6W  
S24 S19  
1957

from which

A Fir 8" dia., bears N.25°E., 27 lks. dist., mkd. ¼ S19 BT

A Fir 10" dia., bears S.67°W., 10 lks. dist., mkd. ¼ S24 BT.

Fd. OK, Nov. 1982, D. Baker, M 93-23

Fd. Ok by Bruce Shaner - Nov. 2000 - C. S. File 65/33-13