

TOWNSHIP 23 RANGE 07 POINT IDENTIFIER # 700400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13 & 24; 18 & 19, T23-6

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 376 survey dated Jan. 22, 1881 (DCSO records Vol. 6 Page(s) 2392)

Set Yew post for cor. secs. 24, 13, 18 and 19, from which
A Cedar 24" dia., bears N.18°E., 62 lks.
A Cedar 20" dia., bears S.10°E., 60 lks.
A Fir 36" dia., bears S.45°W., 56 lks.
A Cedar 10" dia., bears N.58°W., 32 lks.

BLM resurvey by Otis Gould, Joseph Gawron, and Orville Eggen, Cadastral Surveyors, under Group #244, surveyed June 1943/October 1957 (DCSO records Vol. 30 Page(s) 12653)

The Sec. cor., determined at record bearing and distance from the remains of the original bearing trees:

A Fir 50" dia., bears S.45°W., 56 lks. dist., mkd. T23S R7W S24.

A Cedar stump, burned, bears N.58°W., 32 lks. dist., with healed face.

At the corner point

Set an iron post, 3 ft. long, 2" dia., 30" in the ground, with brass cap mkd:

T23S
R7W R6W
S13 S18
S24 S19
1957

from which

A Hemlock 7" dia., bears N.47°30'E., 27 lks. dist., mkd. T23S R6W S18 BT.

A Hemlock 7" dia., bears S.22°30'E., 39 lks. dist., mkd. T23S R6W S19 BT.

A Hemlock 7" dia., bears S.88°W., 26 lks. dist., mkd. T23S R7W S24 BT.

A Hemlock 8" dia., bears N.45°30'W., 21 lks. dist., mkd. T23S R7W S13 BT.

Fd. OK, Nov. 1982, D. Baker, M 93-23