

TOWNSHIP 23 RANGE 07 POINT IDENTIFIER # 700600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 12; 6 & 7, T23-6

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars, Deputy Surveyor under contract # 376 survey dated Jan. 22, 1881 (DCSO records Vol. 6 Page(s) 2393)

-----  
Set Fir post for cor. secs. 12, 1, 6 and 7, from which  
A Maple 12" dia., bears N.10°E., 89 lks.  
A Fir 60" dia., bears S.75°E., 38 lks.  
A Fir 8" dia., bears S.60°W., 26 lks.  
A Fir 16" dia., bears N.80°W., 57 lks.

Wilford N. Haines, #239 - For: Irvin Rice and The Whipple Mill - 1954-55 - C.S. File 42/13

-----  
Found old bearing trees.  
Set an angle iron with brass cap at corner point inscribed:  
"Survey Point-Wilford N. Haines #239"

BLM resurvey by Otis Gould, Joseph Gawron, and Orville Eggen, Cadastral Surveyors, under Group #244, surveyed June 1943/October 1957 (DCSO records Vol. 30 Page(s) 12656)

-----  
The Sec. cor., determined at record bearing and distance from the original bearing trees:  
A Maple stub 14" dia., bears N.10°E., 54 lks. dist., mkd. with partial scribe marks.  
A Fir 77" dia., bears S.75°E., 38 lks. dist., mkd. S7 T23S R6W BT.  
A Fir, dead and burned, 8" dia., bears S.60°W., 26 lks. dist., mkd. with partial scribe marks on open blaze.  
A stump hole, bears N.80°W., 57 lks.

At the corner point  
Set an iron post, 3 ft. long, 2" dia., 30" in the ground, with brass cap mkd:

T23S	
R7W	R6W
S 1	S 6
S12	S 6
1957	

from which  
A W.Fir 15" dia., bears N.36½°E., 76 lks. dist., mkd. T23S R6W S6 BT.  
A Cedar 15" dia., bears S.3°E., 54 lks. dist., mkd. T23S R6W S7 BT.  
A Fir 12" dia., bears S.60°W., 36 lks. dist., mkd. T23S R7W S12 BT.  
A Fir 6" dia., bears N.60°W., 64 lks. dist., mkd. T23S R7W S1 BT.

Fd. OK, March 1991, M 111-72

continued next page

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 12; 6 & 7, T23-6

Alias	Description
Alias	Description
Alias	Description
Alias	Description

<p>Dan Baker - For: Weyerhaeuser Co. - 12/2011 - M163-25 ----- Found - 3/4" BLM Brass cap "1957" 39" W.Fir N.36°E. 51.6' to side/center - 1957 BLM BT 77" Fir, S.75°E., 28.4' to side/center - Orig. BT. 37" Cedar, S.3°E. 35.6' to side/center - 1957 BLM BT 10" Fir, S.5°W., 2.6' to side/center - Lone Rock BT 12" Fir snag, S.60°W., 22.9' - 1957 BLM BT. 8" Fir snag, S.60°W., 18.9' - Orig. BT. 18" Fir, N.64°W., 18.4' to side/center Lone Rock BT. Note - Haines "T" iron per M112-74 bears S.45°14'55"E., 1.82'</p>
<p>Dan Baker - For: Rocking "C" Ranch - 12/2014 - M169-13 ----- Found - 3/4" BLM Brass cap "1957" 25" W.Fir, S.81°W., 30.8' to side/center, 1964 BT 16" W.Fir, S.12°E., 40.0' to side/center, Edwards BT 19" W.Fir, N.42°W., 46.8' to side/center, 1964 BT New - 14" Hemlock, N.81°E., 31.4' to side/center, scribed "T23SR6WS7 BT"</p>
<p>BLM resurvey by Joel R Herzberg, Cadastral Surveyor under Group No. 2778 - surveyed May 2015/July 2016 - (DCSO records Vol. 59 Page(s) 23551 ----- The cor. of secs. 1, 6, 7, &amp; 12, on the W. bdy. of the Tp., perpetuated by Hoffine, in 1991, monumented with an iron post, 2" dia., firmly set, projecting 8" above the ground, with brass cap (properly) mkd. from which the remaining orig. BT reported Gould, in 1943-57 A fir, 77" dia., bears S.75°E., 27.9 ft., with scribe marks 23S R visible on bark. (Record, 25.1 ft.) and the remains of BTs mkd. by Gould, et. al., A fir stump, 41" dia., bears N.36½°E., 50.2 ft., with a healed blaze. A cedar, 37" dia., bears S.3°E., 35.6 ft., with a healed blaze. A decayed fir snag, 12" dia., bears S.62½°W., 22.0 ft., with fragmentary scribe marks visible on partially healed blaze. (Record, S.60°W., 23.8 ft.) and BTs mkd. by Hoffine A fir, 11" dia., bears S.11½°W., 2.9 ft., with a healed blaze. A fir, 18" dia., bears N.64°W., 18.1 ft., with a healed blaze.</p> <p>continued next page</p>

TOWNSHIP 23 RANGE 07 POINT IDENTIFIER # 700600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 12; 6 & 7, T23-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

From this cor., a point erroneously positioned for the cor. of secs. 1, 6, 7, & 12, by Haines, in 1955, bears S.47°22'59"E. 1.90 ft., and was not accepted for the cor., and now functions as a reference monument, monumented with a "T" iron, 3/4" dia., firmly set, projecting 4" above the ground, with a brass washer mkd. WILFORD N HAINES 239 SURVEY POINT DRAIN ORE.

Dan Baker - For: Rocking "C" Ranch - 12/2014 - M169-13

-----  
Found - 3¼" BLM Brass cap "1957"  
39" W.Fir, N.36°E., 51.6' to side/center, 1957 BLM BT  
77" Fir, S.75°E., 28.4' to side/center, orig. BT  
37" Cedar, S3°E., 35.6' to side/center, 1957 BLM BT  
10" Fir, S.5°W., 2.6' to side/center, Lone Rock BT  
12" Fir snag, S.60°W., 22.9', 1957 BLM BT  
8" Fir snag, S.60°W., 18.9', orig. BT  
18" Fir, N.64°W., 18.4' to side/center, Lone Rock BT  
Note - Haines "T" iron per M112-74 bears S.45°14'55"E.,  
1.82'