

TOWNSHIP 23 RANGE 08 POINT IDENTIFIER # 040020

PRIMARY CORNER DESCRIPTION W SW Cor. Gottlib Mehl DLC #40

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Surveys of Donation Land Claims by - Dennis Hathorn, Deputy,  
dated June 8, 1857 - DLC Volume, Page 143

-----  
Marked a Fir 6" dia. for SW. cor., from which  
A Fir 50" dia., bears S.10°E., 19 lks.  
A Maple 12" dia., bears N.50°E., 19 lks.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew  
Jan. 1967 - C.S. File 54/12

-----  
Looked for, not found.

BLM resurvey by Peter A. Peterson, Cadastral Surveyor, under  
Group #640, surveyed July 1967/April 1968 (DCSO records Vol.  
35 Page(s) 14445)

-----  
Point for the exterior cor. on the S. bdy. of claim No. 40,  
determined by the method of irregular boundaries; there is no  
remaining evidence of the original corner.  
Set an iron post, 28" long, 2 1/2" dia., 26" in the ground,  
with brass cap mkd:

T 23 S R 8 W  
|  
S 11 | C 40  
1967

from which

A W. Fir 15" dia., bears N.41°E., 190 lks. dist. mkd. T23S  
R8W C40 BT.

A Fir 10" dia., bears N.56½°W., 48 lks. dist. mkd. T23S  
R8W S11 BT.

Fd. BC & 2 BTs by C. Sweeden, 11/2008 - 2009-0015A