

TOWNSHIP 23 RANGE 08 POINT IDENTIFIER # 040040

PRIMARY CORNER DESCRIPTION S SW Cor. Gottlib Mehl DLC #40

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

Surveys of Donation Land Claims by - Dennis Hathorn, Deputy,
dated June 8, 1857 - DLC Volume, Page 143

Set post SW. cor., from which
A Cedar 24" dia., bears N.45°W., 58 lks.
A Cedar 30" dia., bears S.80°E., 22 lks.

BLM resurvey by Peter A. Peterson, Cadastral Surveyor, under
Group #640, surveyed July 1967/April 1968 (DCSO records Vol.
35 Page(s) 14444-45)

The SW. cor. of DLC #40, determined at record bearing and
distance from the original bearing trees:
A burned Cedar snag 32" dia., bears S.80°E., 22 lks.
dist., with old axe marks visible on opened and rotted
blaze.
A sawed and burned Cedar stump 38" dia., bears N.45°W., 58
lks. dist., with old axe marks visible on opened and
rotted blaze.

At the corner point
Set an iron post, 28" long, 2 1/2" dia., 26" in the ground,
with brass cap mkd: T 23 S R 8 W

S 12 C 40
1967

from which
A Cedar 21" dia., bears N.19°E., 28 lks. dist., mkd. T23S
R8W C40 BT.
A W.Fir 15" dia., bears S.17°W., 67 lks. dist., mkd. T23S
R8W S12 BT.