

TOWNSHIP 23 RANGE 08 POINT IDENTIFIER # 100500

PRIMARY CORNER DESCRIPTION C C for Secs. 7 & 18 only (West)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 6 Page(s) 2548)

-----  
Set a post 4 ft. long and 4" sq., 2 ft. in the ground for cor to secs. 7 & 18, marked S7 on N; S18 on S; T23S R8W on E faces with 2 notches on N & 4 notches on S sides, from which  
A W.Fir 24" dia., bears N.27°E., 88 lks. dist. mkd. T23S R8W S7 BT.  
A W.Fir 40" dia., bears S.65°E., 7 lks. dist. mkd. T23S R8W S18 BT.  
A Fir 24" dia., bears N.57°W., 37 lks. dist. mkd. T23S R8W S7 & 18 BT.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Dec. 1966 - C.S. File 54/12-9

-----  
Found - Orig. 24" now 30" W.Fir 14 ft. high snag, N.27°E., 58.1 ft., previously opened and shows scribe. Also BT scar visible.  
Orig. 24" now 42" Fir, alive, N.57°E., 24.4 ft., shows old scar on edges where someone attempted to cut in and expose scribe.

Set Brass cap at cor. mkd: County Surveyors Office  
T 23 S R9W | S 7 R8W  
CC | S 18  
1966  
New BTs- 12" Hemlock N.36°E. 27.8 ft mkd T23S R8W S7 CC CS BT  
15" D.Fir S.37°E., 9.3 ft. mkd T23S R8W S18 CC CS BT  
Corner lies in flat, swampy area on edge of dense vine-maple.

Cor. Fd. and used in BLM resurvey by James E. Jelley and Rolla R. Steward, Cadastral Surveyors under Group # 703, surveyed July 1969/May 1970 (DCSO records Vol. 35 Pg 14546)

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 8/3/2021 (Filed 11/23/2021) - C.S. File 67/51-14 (2 reports combined)

-----  
Found - 2½" Brass cap on a 1" I.D. iron pipe (properly mkd) plumb and projecting 10" above ground. 1966 DCSO  
48" D.Fir N.57°W., 24.4 ft. fully healed single blaze. OBT 1893  
15" Hemlock snag 35' tall N.36°E., 27.8 ft. partially healed double blaze rotted face no visible scribing. DCSO 1966  
Uprooted 21" D.Fir S.37°E., 9.3 ft. fully healed double blaze. DCSO 1966 Continued next pg

TOWNSHIP 23 RANGE 08 POINT IDENTIFIER # 100500

PRIMARY CORNER DESCRIPTION C C for Secs. 7 & 18 only (West)

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

New - 35" G.Fir S.80°E. 22.7 ft scribed T23S R8W S18 CC BT  
16" Hemlock S.66°W., 32.0 ft. scribed T23S R9W S13  
CS BT.

Note - Flat swampy area now overgrown with brush and many  
large trees.  
Compass decl. 14¾°E.