

PRIMARY CORNER DESCRIPTION Sec. Cor. for 12 & 13 only, T23-9

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by - William H. Byars, Deputy Surveyor, Under Contract No. 279, dated March. 5, 1878 - (DCSO records Vol. 6 Page(s) 2537)

Set a Fir post 4 ft. long, 4" dia., 20" in the ground for the cor. to secs. 7, 12, 13 and 18, from which
A Fir 30" dia., bears N.15°E., 45 lks. dist.
A Chinquapin 12" dia., bears S.52°E., 36 lks. dist.
A Maple 10" dia., bears S.50°W., 15 lks. dist.
A Fir 10" dia., bears N.70°W., 22 lks. dist.

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 6 Page(s) 2530 and 2548)

(Page 2530)
At the cor. to secs. 7, 12, 13 and 18 which is a post 4" sq. mkd. T23S S7 on NE.; R8W S18 on SE.; R9W S13 on SW.; and S12 on NW. faces, with 2 notches on N. and 4 notches on S. edges from which
A Fir 36" dia., bears N.15°E., 45 lks. dist. mkd. T23S R8W S7 BT.
A Chinquapin 16" dia., bears S.52°E., 36 lks. dist. mkd. T23S R8W S18 BT.
A Maple 14" dia., bears S.60°W., 15 lks. dist. mkd. T23S R9W S13 BT.
A Fir 16" dia., bears N.70°W., 12 lks. dist. mkd. T23S R9W S12 BT.
(Page 2548)
The Cor. to secs. 12 and 13, T23S R9W, I obliterate marks on E. of old corner.

BLM resurvey by James E. Jelley and Rolla R. Steward, Cadastral Surveyors under Group # 703, surveyed July 1969/May 1970 (DCSO records Vol. 35 Page(s) 14546-47)

The cor. of secs. 12 and 13 only, determined at record distance from the remains of the original bearing trees:
A sawed Fir stump 36" dia., bears N.12°E., 45 lks. dist., no marks visible. (Rec. N.15°E.)
A Chinquapin root crown 20" dia., bears S.66°E., 36 lks. dist., no marks visible. (Rec. S.52°E.)
and a tree of which I have no record:
A Fir 28" dia., bears S.30°E., 17 lks. dist., with scribe marks T23S R8W S7 BT visible on open blaze.
At the corner point
(Cont. Next Page)

TOWNSHIP 23 RANGE 08 POINT IDENTIFIER # 100514

PRIMARY CORNER DESCRIPTION Sec. Cor. for 12 & 13 only, T23-9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground,
and in a mound of stone, 3 ft. base, to top, with brass cap
mkd:

T 23 S T 23 S

R 9 W R 8 W

S 12 S 7

S 13

1969

from which new bearing trees and a bearing object:

A Hemlock 21" dia., bears S.81°W., 212 lks. dist. mkd.
T23S R9W S13 BT.

A Fir 13" dia., bears N.13°W., 66½ lks. dist. mkd. T23S
R9W S12 BT.

NE. Cor. of Lindy Bridge, bears S.11¼°W., 252 lks. dist.
mkd. with an X chiseled in curb.

The cor. is further substantiated by record calls to Camp
Creek, 350 lks. West, and 320 lks. South.

This cor. was established by Wm. Byars in 1878 as the corner
to secs. 7, 12, 13, and 18, and became a corner of minimum
control during the resurvey of the range line by Whipple in
1894.

Corner Fd. and used in BLM Resurvey by Harvey E. Wofford and
Stephen J. Malloy, Cadastral Surveyors, under Group #1074,
Surveyed July 1980/Nov. 1982 - (DCSO records Vol. 43 Page(s)
16848)

Fd. OK April 1994 by C. Mulkins - M 118-71