

TOWNSHIP 23 RANGE 08 POINT IDENTIFIER # 100700

PRIMARY CORNER DESCRIPTION NW Cor. of T23S R8W (NW Cor. Sec. 6)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM resurvey by Harvey E. Wofford and Stephen J. Malloy, Cadastral Surveyors, under Group #1074, surveyed July 1980/Nov. 1982 - (DCSO records Vol. 43 Page(s) 16851-52)

True point for the NW. cor. of T23S R8W.
Set an alum. post, 28" long, 2½" dia., 24" in the ground, with alum. cap mkd:

| | | |
|--------|--|--------|
| | | T 22 S |
| | | R 9 W |
| T 23 S | | S 36 |
| R 9 W | | T 23 S |
| S 1 | | R 8 W |
| | | S 6 |

1980

from which

- A Fir 4" dia., bears S.60¼°E., 58 lks. dist. mkd. X BT.
- A Fir 10" dia., bears S.23½°E., 44 lks. dist. mkd. T23S R8W S6 BT.

From this point, the original NW. cor. of T23S R8W, bears S.89°51'W., 0.14 chs. dist., perpetuated and recorded by Godfrey, in 1963, monumented with an iron post, 1½" dia., firmly set, projecting 7" above ground with 1963 county brass cap, from which the remains of an original bearing tree:

- A Fir stump 47" dia., bears N.40°W., 1 lks. dist., rescribed T23S R9W S1 CS BT by Godfrey.
- and a bearing tree mkd. by Godfrey:
 - A Fir 18" dia., bears S.71°E., 85 lks. dist., with healed blaze.
- and a bearing tree mkd. by Vernon Tracy in 1966:
 - A Fir 15" dia., bears N.49°E., 40 lks. dist., with healed blaze.