TOWNSHIP 23 RANGE 08 POINT IDENTIFIER # 139100

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. for Sec. 6, T24-8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 6 Page(s) 2538)

Top of ridge, course N.80°W., Set a post 4 ft. long, 4" sq., 24" in the ground for ¼ sec. corner marked ¼ S on N. face, from which

A Fir 24" dia., bears N.26°E., 53 lks. dist. mkd. ¼ S BT.
A Hemlock 12" dia., bears S.26°E., 33 lks. dist. mkd. ¼ S BT.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Jan. 1967 - C.S. File 54/12-18

Found - Orig. 24" now 34" Fir snag, N.26°E., 35.0 ft., open and find "S" scribe very lightly cut into face.
Orig. 12" now 26" Hemlock, turned out and lying face down, S.26°E., 21.8 ft.

Set Brass cap at cor. mkd: County Surveyors Office

¼ S 6 T 23 S T 24 S R 8 W 1967

New BTs- 13" Hemlock S.8°E., 26.5 ft. mkd. ¼ S6 CS BT.
8" Hemlock S.45½°W., 29.7 ft. mkd. ¼ S6 CS BT.

Corner lies nearly on top of ridge, course E-W.

Tony Hostetter - For: Weyerhaeuser - Jan. 2004 - C.S. File 65/49-12

Found - 1967 brass cap by Douglas Co. Surveyor as described by Tracy in 1967
Both BTs marked Tracy in 1967 are stumps.

WEYCO BTs -
22" Hemlock, WEYCO tag, bears N.60°E., 4.7 ft to "W" nail.
10" Hemlock, WEYCO tag, bears S.34°W., 23.3 ft to "W" nail.

New BTs- 6" Fir, scribed "S6 ¼ BT" WEYCO tag, bears S.13°E., 19.7 ft. to spike placed in root collar below scribing.