

TOWNSHIP 23 RANGE 08 POINT IDENTIFIER # 140600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 6 and 7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 6 Page(s) 2610)

Set a post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. marked ¼ S on N. face, from which
A Fir 6" dia., bears N.46°W., 39 lks. dist. mkd. ¼ S BT
A Fir 40" dia., bears S.3°E., 62 lks. dist. mkd. ¼ S BT

BLM survey by Harvey E. Wofford, Cadastral Surveyor, under Group #1005, surveyed July/Dec. 1980 - (DCSO records Vol. 43 Page(s) 16833)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 23 S R 8 W
1/4 $\frac{S}{S}$ $\frac{6}{7}$
1980

from which

A Fir 23" dia., bears S.43 3/4°E., 47 lks. dist. mkd. ¼ S7 BT.

A Fir 28" dia., bears N.69°W., 69 lks. dist. mkd. ¼ S6 BT