

TOWNSHIP 23 RANGE 08 POINT IDENTIFIER # 140700

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. Sec. 6 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

BLM survey by Harvey E. Wolford, Cadastral Surveyor, under Group #1005, surveyed July/Dec. 1980 - (DCSO records Vol. 43 Page(s) 16836-37)

-----  
The point for the ¼ sec. cor. of sec. 6 only, T23S R8W, is at proportionate dist. on the N. bdy. of sec. 6.  
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 22 S R 8 W  
1/4 S 6  
T 23 S R 8 W  
1980

from which

- A Fir 5" dia., bears S.59½°E., 11 lks. dist. mkd. X BT.
- A Fir 8" dia., bears S.46½°W., 123½ lks. dist. mkd. ¼ S6 BT.

From this point, the ¼ sec. cor. of sec. 31 only, T22S R8W, bears N.89°59'W., 1.42 chs. dist.