

PRIMARY CORNER DESCRIPTION Sec. Cor. for 5 & 6 only, T24-8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 6 Page(s) 2538)

Set a sandstone 14x10x8 ins., 9" in the ground for corner to secs. 5 and 6, marked with 1 notch on W. and 5 notches on E. edges, from which
A Hemlock 6" dia., bears S.27°E., 26 lks. dist. mkd. T24S R8W S5 BT.
A Fir 40" dia., bears S.70°W., 30 lks. dist. mkd. T24S R8W S6 BT.
A Hemlock 14" dia., bears N.57°W., 25 lks. dist. mkd. T24S R8W BT.

Douglas Co. Surveyors Office - V.R. Tracey and crew - Jan. 21, 1967 - C.S. File 54/12-2

From cor. of Secs. 31 and 32 of T23-8, we go West 50.2 ft. and find the following possible BTs,
40" Fir stump S.70°W., 19.8 ft. We chop open and find old axe face and notches but no scribe marks.
26" hemlock stump, N.57°W., 16.5 ft. Chop open and find axe marks and no scribe marks.
Both stumps fit good for bearing and distance as called for in original notes.
Did Not Renew.

Tony Hostetter - For: Weyerhaeuser Co. - July 2003 - M142-67

Found - ¾" iron pipe, set by Weyerhaeuser Co.
40" Fir stump, face evident, OBT, bears S.66°40'W., 19.8 ft.
26" Hemlock stump, face evident, OBT, bears N.59°25'W., 16.2 ft.
New BTs- 12" Fir, scribed "S4 NW BT" bears N.05°E., 7.6 ft. to spike.
14" Fir, scribed "S5 NW BT" bears S.70°E., 12.5 ft. to spike.