

TOWNSHIP 23 RANGE 08 POINT IDENTIFIER # 200240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 29 and 30

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 6 Page(s) 2600)

-----  
Set a post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. marked ¼ S on W. face, from which  
A Hemlock 12" dia., bears S.66½°W., 28 lks. dist. mkd. ¼ S BT.  
A Chittenwood, 5" dia., bears N.47°E., 13 lks. dist. mkd. ¼ S BT.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Oct. 1967 - C.S. File 54/12-68

-----  
Found Orig. 12" now 30" Hemlock, alive, S.66½°W., 18.5 ft. Opened this tree in spring of this year and did not find any scribe. Did not feel this was original tree. However, later this year, Coos Bay BLM found fragmentary scribe and axe notch. We now verify this to be original BT.  
Set Brass cap at cor. mkd: County Surveyors Office  
T 23 S R 8 W  
¼ S30|S29  
1967  
New BTs- 26" D.Fir N.87°W., 21.6 ft. mkd. ¼ S30 CS BT.  
20" Hemlock S.31°E., 30.8 ft. mkd. ¼ S29 CS BT.  
No trace of other original BTs.  
Corner lies on very steep easterly slope.