

TOWNSHIP 23 RANGE 08 POINT IDENTIFIER # 200300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19, 20, 29 and 30

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 6 Page(s) 2600)

Set a post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 19, 20, 29 and 30, marked T23S S20 on NE.; R8W S29 on SE.; S30 on SW.; and S19 on the NW. faces, with 2 notches on S. and 5 notches on E. edges, from which
A Chinquapin 9" dia., bears N.58°E., 22 lks. dist. mkd. T23S R8W S20 BT.
A Chinquapin 14" dia., bears S.74°E., 27 lks. dist. mkd. T23S R8W S30 BT.
A Laurel 14" dia., bears S.73°W., 35 lks. dist. mkd. T23S R8W S30 BT.
A Chinquapin 9" dia., bears N.53°W., 12 lks. dist. mkd. T23S R8W S19 BT.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Jan/Feb. 1967 - C.S. File 54/12-49

Found - Orig. 9" now 15" Chinquapin, N.58°E., 14.5 ft., now snag, scribe "S3 8W 20" visible on unhealed blaze, face badly decayed.
Orig. 14" now 24" Chinquapin S.74°E., 17.8 ft., alive, shows good scar. Do not open.
Orig. 9" now 16" Chinquapin, N.53°W., 7.9 ft., alive, blaze never healed. Tree now hollow.
No trace original SW. BT.

Set Brass cap at cor. mkd: County Surveyors Office
T 23 S R 8 W
S 19 | S 20
S 30 | S 29
1967

New BTs- 5" W.Fir S.45°E., 7.7 ft. mkd. S29 CS BT.
14" Chinquapin N.83°W., 3.5 ft. mkd. T23S R8W S19 CS BT.
5" W.Fir N.45°E., 19.3 ft. mkd. S20 CS BT.
6" D.Fir S.60°W., 23.4 ft. mkd. S30 CS BT.
This corner lies on very steep, SW. slope.