TOWNSHIP 23 RANGE 08 POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7, 8, 17 and 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 6 Page(s) 2605-06)

Set post 4 ft. long, 4" sq., for cor. to secs. 7, 8, 17 and 18, 2 ft. in ground, marked T23S S8 on NE.; R8W S17 on SE.; S18 on SW.; S7 on NW. faces with 4 notches on S. and 5 notches on E. edges, from which

A Maple 14" dia.,bears N.89°E., 39 lks. dist. mkd. T23S R8W S8 BT.

A Maple 12" dia., bears S.63°E., 48 lks. dist. mkd. T23S R8W S17 BT.

A Maple 20" dia., bears S.69°W., 82 lks. dist. mkd. T23S R8W S18 BT.

A Fir 40" dia., bears N.52°W., 60 lks. dist. mkd. T23S R8W S7 BT.

BLM survey by Harvey E. Wofford, Cadastral Surveyor, under Group #1005, surveyed July/Dec. 1980 - (DCSO records Vol. 43 Page(s) 16828-29)

Point for the sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an alum. post, 28" long, 2 1/2" dia., 24" in the ground, with alum. cap mkd:

T 23 S R 8 W
S 7 S 8
S 18 S 17
1980

from which

A Fir 9" dia., bears N.45°E., 19 lks. dist. mkd. T23S R8W S8 BT.

A Fir 10" dia., bears S.10½°E., 54 lks. dist. mkd. T23S R8W S17 BT.

A Fir 10" dia., bears S.43½°W., 71 lks. dist. mkd. T23S R8W S18 BT.

A Fir 8" dia., bears N.46°W., 5 lks. dist. mkd. T23S R8W S7 BT.