

TOWNSHIP 23 RANGE 08 POINT IDENTIFIER # 200540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 7 and 8

|       |       |             |       |
|-------|-------|-------------|-------|
| Alias | _____ | Description | _____ |
| Alias | _____ | Description | _____ |
| Alias | _____ | Description | _____ |
| Alias | _____ | Description | _____ |

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 6 Page(s) 2608)

-----  
Set a post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. marked ¼ S on W. face, from which  
A Fir 14" dia., bears N.72°E., 63 lks. dist. mkd. ¼ S BT  
A Fir 14" dia., bears S.54°W., 28 lks. dist. mkd. ¼ S BT

BLM survey by Harvey E. Wofford, Cadastral Surveyor, under Group #1005, surveyed July/Dec. 1980 - (DCSO records Vol. 43 Page(s) 16831)

-----  
Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 23 S R 8 W  
1/4  
S 7 S 8  
1980

from which

A Fir 14" dia., bears N.42°E., 44½ lks. dist. mkd. ¼ S8 BT  
A Fir 10" dia., bears N.45½°W., 26½ lks. dist. mkd. ¼ S7 BT.