

TOWNSHIP 23 RANGE 08 POINT IDENTIFIER # 200700

PRIMARY CORNER DESCRIPTION C C for Secs. 5 & 6 only, (North)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 6 Page(s) 2611)

-----  
Intersect No. bdy. of T23S R8W, 1.46 chs. East of cor. to secs. 31 and 32 of T22S R8W, at which point, I set a post 4 ft. long, and 4" sq., 2 ft. in the ground for closing cor. to secs. 5 & 6, mkd. S5 on East, C C T23S R8W on S., and S6 on W. faces, with 5 notches on E. and 1 notch on W sides, from which

- A Fir 6" dia., bears N.40°E., 52 lks. dist. mkd. T23S R8W S5 BT.
- A Fir 8" dia., bears S.20°W., 41 lks. dist. mkd. T23S R8W S6 BT.
- A Fir 40" dia., bears N.44°W., 60 lks. dist. mkd. T23S R8W CC S5 & 6 BT.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Mike Stone & Vernon Ray Tracy, crew - Dec 1962/Jan. 1963 - C.S File 52/14-52

-----  
Found - 58" Fir N.36°W. (Not N.44°W.) 39.6 ft. Cut open scar and found good scribing. Tree alive and in good condition.

34" Fir S.20°W., 27.1 ft., shows very good axe scar. Badly rotted W.Fir stump N.40°E., 34.3 ft. Portion of flat face and axe marks, but no scribing.

Set Brass cap at cor. mkd: County Surveyors Office  
T 22 S  
CC  
S 6 | S 5  
T 23 S R 8 W  
1963

New BT - 10" D.Fir S.74°E., 27.0 ft. mkd. T23S R8W CC S5 CSBT  
Found 1¼" I.P. 15" above ground with cap stamped, probably set by LongBell Lbr., N.86°E., 3.2 ft. from corner as set above.

BLM resurvey by Floyd A. Brooks and James E. Jolley, Cadastral Surveyors, under Group #'s 514 and 350, surveyed June 1963/March 1965 (DCSO records Vol. 33 Page(s) 13673-74)

-----  
The closing cor. of secs. 5 and 6, T23S R8W, remonumented by the county surveyor in 1963, with an iron post 1½" dia., 6" above ground, firmly set, with 1963 brass cap. from which the original bearing trees mkd. by Whipple in 1894:

(Cont. Next Page)

TOWNSHIP 23 RANGE 08 POINT IDENTIFIER # 200700

PRIMARY CORNER DESCRIPTION C.C. for Secs. 5 & 6 only, (North)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A decayed Fir stump size indeterminate, bears N.42½°E., 52 lks. dist. with no marks remaining. (Rec. brg. N.40°E.)  
A Fir 40" dia., bears S.22½°W., 41 lks. dist. with a healed blaze. (Rec. brg. S.20°W.)  
A Fir 60" dia., bears N.42½°W., 60 lks. dist. with a healed blaze. (Rec. brg. N.44°W.)  
and a tree mkd. by the County Surveyor  
A Fir 10" dia., bears S.75½°E., 41 lks. dist. with scribe marks T23S R8W CC S5 CS BT visible on unhealed blaze.  
Add the marks BLM 1963 to the brass cap.  
From this point, an iron post 1½" dia., 12" above ground, firmly set, bears East, 0.05 chs. dist. with brass cap mkd.

S 32  
S6|S5

BLM resurvey by Harvey E. Wofford, Cadastral Surveyor, under Group #1005, surveyed July/Dec. 1980 (DCSO records Vol. 43 Page(s) 16836)

-----  
The closing cor. of secs. 5 & 6, perpetuated and recorded by Godfrey in 1963, redescribed by Brooks and Jelley in 1963-65, monumented with an iron post 1½" dia. firmly set, projecting 6" above ground with 1963 county brass cap.

from which the remaining original bearing trees  
A Fir 38" dia., bears S.22½°W., 41 lks. dist. with healed blaze.  
A Fir 60" dia., bears N.36°W., 60 lks. dist. with healed blaze. (Rec, N.42½°W.)  
and a bearing tree mkd. by Godfrey  
A Fir 13" dia., bears S.75½°E., 41 lks. dist. with healed blaze.

From this point, a local cor. recorded by Brooks and Jelley in 1963-65, monumented with an I.P. 1½" dia., firmly set, projecting 15" above ground, with Iron cap mkd. S5 S6 S32, bears East, 0.05 chs. dist.

From this same point, the cor. of secs. 31 and 32 only, T22S R8W, bears N.89°37'W., 1.47 chs. dist.