

TOWNSHIP 23 RANGE 08 POINT IDENTIFIER # 240300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 20 and 29

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 6 Page(s) 2601)

Set a stone 12x10x6 ins., 8" in ground for ¼ sec. cor. marked ¼ on N. face, from which
A Fir 40" dia., bears N.2°W., 60 lks. dist. mkd. ¼ S BT.
A Chinquapin 12" dia., bears S.56°E., 22 lks. dist. mkd. ¼ S BT.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew
April 1966 - C.S. File 54/12-35

Found - Stone at corner 14" x 12" x 7", marked "¼" on N. face, firmly set, as called for in orig. field notes.

Orig. 40" now 60" Fir, N.2°W., 39.6 ft., shows good scar, alive, we do not open.

No trace of other original BTs.

Set Brass cap at cor. mkd: County Surveyors Office
T 23 S R 8 W

¼ $\frac{S \ 20}{S \ 29}$
1966

Reset stone alongside.

New BTs- 5" Hemlock N.78°W., 15.8 ft. mkd. ¼ S20 CS BT.

25" Chinquapin N.36°E., 30.4 ft. mkd. ¼ S20 CS BT.

Corner lies on top of ridge, course NW. and SE.