

TOWNSHIP 23 RANGE 08 POINT IDENTIFIER # 240400

PRIMARY CORNER DESCRIPTION 1/4 cor. for Secs. 17 and 20

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 6 Page(s) 2604)

-----  
Set a post 3 ft. long, 3" sq., 2 ft. in the ground for 1/4 sec. cor. marked 1/4 S on N. face, from which  
A Fir 12" dia., bears N.30°W., 90 lks. dist. mkd. 1/4 S BT  
A Laurel 8" dia., bears S.21°E., 24 lks. dist. mkd. 1/4 S BT

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew  
June 1965 - C.S. File 54/12-34

-----  
Found - Orig. 12" now 28" Fir, N.30°W., 59.4 ft. open and find partial "S" and notch at bottom of face, BT is down.

No trace other original BT.

Set Brass cap at cor. mkd: County Surveyors Office

T 23 S R 8 W

1/4 S 17

S 20

1965

New BTs- 16" D.Fir N.8°E., 36.2 ft. mkd. 1/4 S17 CS BT.

6" D.Fir S.3°E., 15.4 ft. mkd. 1/4 S20 CS BT.

Corner lies on S. edge of Jeep road bears S.55°E.