

TOWNSHIP 23 RANGE 08 POINT IDENTIFIER # 300140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 32 and 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 6 Page(s) 2586)

Set a stone 12x10x5 ins., 8" in the ground for ¼ sec. cor. mkd. ¼ on W. face, from which
A Fir 30" dia., bears S.18°E., 54 lks. dist. mkd. ¼ S BT
A Fir 30" dia., bears N.22°W., 27 lks. dist. mkd. ¼ S BT

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew
Jan. 1967 - C.S. File 54/12-52

Found - Sandstone 13"x8"x5" mkd. "¼" on W. face, firmly set.
Orig. 30" now 36" Fir, alive, S.18°E., 35.6 ft., shows "¼ S BT" bark scribe in fair condition.
Orig. 30" now 36" Fir, alive, N.22°W., 17.8 ft., shows good scar. We do not open.

Set Brass cap at cor. mkd: County Surveyors Office
T 23 S R 8 W
¼ S32|S33
1967

New BTs- 15" Yew S.10°W., 41.5 ft. mkd. ¼ S32 CS BT.
5" Yew N.69°E., 2.7 ft. mkd. ¼ S33 CS BT.

Corner lies on steep, West slope, approx. 200 ft. North of E-W cutting linge, cut off to South.