

TOWNSHIP 23 RANGE 08 POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 28, 29, 32 and 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 6 Page(s) 2586)

Set a stone 14 x 12 x 10 ins., 10" in the ground for cor. to secs. 28, 29, 32 and 33, mkd. with 1 notch on S. and 3 notches on E. edges, from which

- A Fir 12" dia., bears N.12°E., 14 lks. dist. mkd. T23S R8W S28 BT.
- A Cedar 10" dia., bears S.53°E., 37 lks. dist. mkd. T23S R8W S33 BT.
- A Fir 14" dia., bears S.20°W., 21 lks. dist. mkd. T23S R8W S32 BT.
- A Hemlock 4" dia., bears N.39°W., 12 lks. dist. mkd. T23S R8W S29 BT.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Jan. 1967 - C.S. File 54/12-44

Found - Corner stone 14"x12"x9" mkd. with 4 notches E. and 1 notch S., firmly set.
Orig. 12" now 13" Fir snag, N.12°E., 9.2 ft., scribe "T23S R8W S28" visible on unhealed blaze.
Orig. 10" now 20" Cedar, alive, S.53°E., 24.4 ft., shows faint scar. Rescribe "T23S R8W S33 CS BT"
Orig. 14" now 22" Fir, alive, S.20°W., 13.9 ft., shows fair scar. Rescribe "T23S R8W S32 CS BT"
Orig. 4" now 6" Hemlock, alive, N.39°W., 7.9 ft., shows scar, we open and find "S29" scribe.

Set Brass cap at cor. mkd: County Surveyors Office

T 23 S R 8 W
S 29 | S 28
S 32 | S 33
1967

New BTs- 14" Cedar N.52°E., 41.3 ft. mkd. T23S R8W S28 CS BT.
6" Hemlock N.79°W., 25.1 ft. mkd. T23S R8W S29 CSBT.
Corner lies on N. slope 30 ft. N. of bench.