

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 28 and 29

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 6 Page(s) 2588)

-----  
This point falling on bed rock, I made a (X) cross at exact cor. point with 1/4 on W. for 1/4 sec. corner, from which  
A Fir 8" dia., bears S.82°E., 7 lks. dist. mkd. 1/4 S BT.  
A Fir 10" dia., bears N.45°W., 9 lks. dist. mkd. 1/4 S BT.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew  
Jan. 1967 - C.S. File 54/12-45

-----  
Found - "1/4 +" on nearly vertical rock face.  
Orig. 8" Fir now 9", 10 ft. high snag, S.82°E., 4.6 ft., previously opened and shows "1/4" scribe. We chop lower scar and find "B".  
Orig. 10" now 16" Fir, alive, N.45°W., 5.9 ft. Do not open.

Impossible to set Brass cap at exact corner point so  
SET Witness Corner 10 ft. North - brass cap marked:  
County Surveyors Office  
T 23 S R 8 W  
W.C. 10 ft. S. to cor.  
1/4 S 29 | S 28  
1967

New BTs- 13" D.Fir S.64°E., 21.7 ft. mkd. W.C. 1/4 S28 CS BT.  
15" D.Fir N.65°W., 8.5 ft. mkd. W.C. 1/4 S29 CS BT.  
Corner lies 50 ft. S. of foot of bluff, 30 ft. high and 50 ft. N. of bottom of small draw.

Fd. OK March 1982 by L. Roberts - M 92-3

BLM resurvey by John A. Farmer, Cadastral Surveyor, under Group #1336, Surveyed Aug/Oct. 1986 - (DCSO records Vol. 48 Page(s) 18287)

-----  
The 1/4 sec. cor., mkd. with the original cross (X) and 1/4 on near vertical face of exposed bedrock, approx. 10 ft. high, 40 ft. long, bears N.20°W. and S.20°E.

At the corner point  
Set an iron post, 28" long, 1" dia., 6" in drill hole in solid rock, with brass cap mkd:

T 23 S R 8 W  
1/4  
S 29 | S 28  
1986

from which  
(Cont. Next Page)

TOWNSHIP 23 RANGE 08 POINT IDENTIFIER # 300240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 28 and 29

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Fir 31" dia., bears S.69¼°E., 28 lks. dist. mkd. ¼ S28  
BT.

A Fir 25" dia., bears S.16°W., 29 lks. dist. mkd. ¼ S29  
BT.

From this point, a witness cor. to the ¼ sec. cor., established and recorded by Tracy in 1967, bears North, 0.150 chs. dist., monumented with an iron post 1½" dia., firmly set, projecting 8" above ground with brass cap mkd. in 1967 from which bearing trees mkd. by Tracy:

A Fir 15" dia., bears S.62½°E., 33 lks. dist., with healed blaze.

A Fir 16" dia., bears N.71°W., 13 lks. dist., with healed blaze.