

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 20 and 21

Alias	Description
Alias	Description
Alias	Description
Alias	Description

<p>GLO survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 6 Page(s) 2590)</p> <p>-----</p> <p>Set a stone 12x10x6 ins., 8" in ground, marked ¼ on W. face, from which</p> <p> A Fir 24" dia., bears N.9°E., 60 lks. dist. mkd. ¼ S BT.</p> <p> A Fir 14" dia., bears N.50°W., 27 lks. dist. mkd. ¼ S BT.</p>
<p>Douglas Co. Surveyors Office - John M. Powell, and crew - March 15, 1971 - C.S. File 54/12-71</p> <p>-----</p> <p>Found - 24" Fir stump, burnt out, N.9°E., 39.6 ft.</p> <p> Also unrecorded 1½" O.D. Iron pipe set at approx. ¼ cor. Probably set by International Paper.</p> <p> Slide area where other BT stood.</p> <p> No original evidence.</p>
<p>Survey by Les Roberts - For: International Paper Co. - March 1979 - M 76-21</p> <p>-----</p> <p>Found - 3/4" Iron pipe and 12" x 10" x 6" stone.</p> <p> 28" burned out stump, N.12°E., 39.3 ft.</p> <p>Drove 1½" Iron pipe and brass cap over existing 3/4" Iron pipe.</p>
<p>Ron Rice - April 25, 2013 - C.S. File 65/78-40 & C.S. File 65/81-13 3/2014</p> <p>-----</p> <p>Found - 2½" brass cap, dated 1979, with stone adjacent and the following accessories:</p> <p> 16" D.Fir bears S.82°W., 7.4 ft. - healed face (Roberts 1979)</p> <p> 19" D. Fir bears S.42°E., 19.6 ft. - healed face (Roberts 1979)</p> <p> 28" burned out stump bears N.12°E., 39.3 ft.</p> <p>New - 22" D.Fir bears S.2°W., 31.5 ft. - blazed, scribed ¼ S20 BT</p> <p> 24" D.Fir bears N.16°E., 20.5 ft. - blazed, scribed ¼ S21 BT</p> <p>Note - Corner has steel post adjacent to it. All BTs have red painted bands and yellow tags.</p> <p> Compass Declination 16° East</p>