

TOWNSHIP 23 RANGE 08 POINT IDENTIFIER # 300440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 16 and 17

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 6 Pg 2592)

Set a post 3 ft. long, 3" sq., 2 ft. in the ground marked ¼ S on W. face, from which
A Laurel 8" dia., bears N.46°W., 9 lks. dist. mkd. ¼ S BT
A Laurel 6" dia., bears N.81°E., 15 lks. dist. mkd. ¼ S BT

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Dec. 1966 - C.S. File 54/12-42A

Looked for, not found.

Clyde Mulkins - For: IP Timberlands - March 1995/May 2015 - M169-50 (filed 7/2/2015)

Set - An I.P.T.O. alum. monument at the ¼ corner from which:
I scribed ¼ S17 BT" on a 15" DF bears N.50°W. 10.5 ft.
I scribed "¼ S17 BT" on a 16" DF bears north 39.0 ft.
I scribed "¼ S16 BT" on a 14" DF bears S.81°E. 9.8 ft.
I scribed "¼ S16 BT" on a 13" DF bears S19°E. 11.7 ft.

BLM dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2781, surveyed May/Aug. 2015 - (DCSO records Vol. 58 Page(s) 23415)

The ¼ sec. cor. of secs. 16 & 17, reestablished by proportionate measurement by Mulkins, PLS No. 2006, in 1995, filed in 2015. There is no remaining evidence of the original cor., therefore this point is accepted as the cor.; monumented with an aluminum rod, 3/4" dia., firmly set, projecting 6" above ground, with an aluminum cap (properly) mkd.

from which the bearing trees mkd. by Mulkins
A fir, 18" dia., bears S.80°E., 9.8 ft., with a healed blaze and a nail at the base on the right side center.
A fir, 16" dia., bears S.5°E., 11.8 ft., with a healed blaze and a nail at the base on the right side center.
A fir, 19" dia., bears N.53½°W., 10.4 ft., with a healed blaze and a nail at the base on the left side center.
A fir, 19" dia., bears N.1/2°W., 38.7 ft., with a healed blaze and a nail at the base on the left side center.
An aluminum fence post is alongside the cor..
From this cor., the steel fence post reported by Mulkins bears S.58°47'54"W., 5.40 ft.
A search was made for all original line trees bet. secs. 16 and 17 and none were recovered.