

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 8 and 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 6 Page(s) 2594)

Set a post 3 ft. long, 3" sq., 2 ft. in the ground for ¼ sec. cor. marked ¼ S on W. face, from which
A Fir 10" dia., bears S.38°E., 26 lks. dist. mkd. ¼ S BT
A Fir 38" dia., bears N.19°W., 67 lks. dist. mkd. ¼ S BT

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Dec. 1966 - C.S. File 54/12-42

Found - Orig. 10" now 18" Fir, S.38°E., 17.2 ft., now down, open and find "¼S" scribe and reverse.
Orig. 38" now 48" Fir, alive, N.19°W., 44.2 ft., fragmentary bark scribe on old bark blaze.
Set Brass cap at cor. mkd: County Surveyors Office
T 23 S R 8 W
¼ S 8 | S 9
1966

New BTs- 17" D.Fir S.36°E., 30.1 ft. mkd. ¼ S9 CS BT.
15" Chinquapin S.66°W., 33.0 ft. mkd. ¼ S8 CS BT.
Corner lies on steep West slope in reproduction of small Fir and Hemlock.

Ronald L. Rice, Ward NW - Aug. 8, 2008 - C.S. File 65/63-27

Found - 3" brass cap (properly mkd) dated 1966 with the following accessories:
20" D.Fir bears S.36°E., 30.1' - healed face
13" D.Fir bears N.56°E., 33.5' - healed face (not of record)
19"x4' D.Fir stump bears S.26°W., 50.0' - healed face (not of record)
16"x4' D.Fir stump bears S.83°W., 21.4' - healed face (not of record)
Note - Corner has steel post adjacent to it. All BTs have red painted bands & yellow tags.
Compass decl. 17°E.