

TOWNSHIP 23 RANGE 08 POINT IDENTIFIER # 300628

PRIMARY CORNER DESCRIPTION Line Tree Between Secs. 4 & 5 (AP)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 6 Page(s) 2596)

A fir, 60" dia.

BLM resurvey by Michael O. Jones, Cadastral Surveyor under special instructions dated May 27, 2009 - Surveyed June/July 2009 - (DCSO records BLM plat 2011 & Vol. 56 Page 22267)

The remains of an original line tree on the line between secs. 4 and 5; monumented with a sawed fir stump, 74" dia. 6 ft. high, mkd. with 2 notches on the N. side and 2 rotten notches on the S. side, and red paint under the moss on the stump, and is accepted as an angle point on the line bet. secs. 4 and 5.
At the corner point
Drive an aluminum rod, 36" long, 1/2" dia., 36" in the center of the stump, with aluminum cap mkd.
AP
S 5 | S 4
2009
from which
A fir, 7" dia., bears N.87°E., 20.6 lks., mkd: AP S4 BT.
A maple, 11" dia., bears S.69°W., 13.6 lks., mkd: AP S5 BT.

Fd per rec. 8/2019 - C.S. File 65/102-73 by R. Quimby