

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 4 and 5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 6 Page(s) 2596)

Set a post 3 ft. long, 3" sq., 2 ft. in ground for ¼ sec. cor. marked ¼ S. on W. face, from which
A Maple 8" dia., bears S.15°E., 35 lks. dist. mkd. ¼ S BT.
A Maple 12" dia., bears N.38°W., 28 lks. dist. mkd. ¼ S BT

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew
Feb. 1967 - C.S. File 54/12-25A

Looked for, Not found.

BLM resurvey by Michael O. Jones, Cadastral Surveyor under special instructions dated May 27, 2009 - Surveyed June/July 2009 - (DCSO records BLM plat 2011 & Vol. 56 Page 22267)

Point for the ¼ sec. cor. of secs. 4 and 5, at proportionate distance between the original line tree bet. secs. 4 and 5 and the closing cor. of secs. 4 and 5 on the N. bdy. of the Tp.; there is no remaining evidence of the original corner. Set a stainless steel post, 28" long, 2½" dia., 22" in the ground, with brass cap mkd.

T23S R8W

¼

S 5 | S 4

2009

from which

A fir, 9" dia., bears S.27°E., 18.8 lks., mkd: ¼ S4 BT.

A fir, 14" dia., bears N.63°W., 18.1 lks., mkd: ¼ S5 BT.

Deposit a magnet in a white plastic case at the base of stainless steel post.

Ron Quimby - Crew: N. Fromdahl & J. Ogden - 8/2019 - C.S. File 65/102-72

Found - BLM brass cap (properly mkd) on 2½" iron pipe (BLM)
Down 9" Fir S.27°E., 12.4 ft.

19" fir N.63°W., 11.9 ft (good scar)

New - 18" D.Fir N.84°W., 24.2 ft. scribed ¼ S5 BT.

14" D.Fir S.78°E., 42.7 ft. scribed ¼ S4 BT.

6' post S.62°E., 5.0 ft.

Note - Compass decl. 15½°E.