

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 33 only, T22-8

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 376 survey dated Jan. 22, 1881 (DCSO records Vol. 4 Pg 1593)

Set post for ¼ sec. cor., from which
A Hemlock 10" dia., bears N.40°W., 21 lks. dist.
A Fir 36" dia., bears S.50°W., 43 lks. dist.

BLM resurvey by Floyd A. Brooks, Cadastral Surveyor, under Group #436, Surveyed May\June 1962 (DCSO records Vol. 31 Page(s) 13104)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 26" in the ground, with brass cap mkd:
T 22 S R 8 W
¼ S 33
1962

from which
A Fir 4" dia., bears N.76½°E., 38½ lks. mkd. ¼ S33 BT.
A Fir 12" dia., bears N.6°W., 32 lks. mkd. ¼ S33 BT.

Rob Ward, Ward North West Inc. - Witness: Ron Rice - 6/15/2000 - C.S. File 65/30-22

Found - 3¼" BLM Brass cap
17" G.Fir bears N.76½°E., 25.4 ft. healed face.
24" D.Fir bears N.6°W., 21.1 ft. healed face.
New - 13" G.Fir bears S.3°W., 6.0 ft. blazed & scribed X BT.
22" D.Fir bears S.31°E. 16.5 ft. blazed & scribed X BT.
Note - All BTs have red painted bands and faces plus yellow BT tags. Steel post set adjacent to corner.

Ron Rice - Josh Reed - 7/8/2010 - C.S. File 65/69-39

Condition report only
Found - 3¼" BLM brass cap dated 1962 with the following accessories:
26" D.Fir bears N.6°W., 21.1' - healed face.
22" W.Fir bears N.76½°E., 25.4' - healed face.
14" W.Fir bears S.3°W., 6.0' - healed face.
22"x6' D.Fir stump bears S.31°E., 16.5' - scribing visible.
Note - Corner has steel post adjacent to it. All BTs have red painted bands & yellow tag.

