

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 6 Page(s) 2540)

-----  
Set a sandstone 18x12x6 ins., 12" in the ground for ¼ sec. cor. marked ¼ S on N. face, from which  
A Fir 10" dia., bears N.87°W., 46 lks. dist. mkd. ¼ S BT  
A Fir 14" dia., bears S.34°E., 17 lks. dist. mkd. ¼ S BT

Survey by Louis Prahar - For: Weyerhaeuser Co. - Aug. 1966 - C.S. File 55/11

-----  
Found - 1894 rock with ¼ on N. side.  
1894 BT, now a windfall lying Eastward with face up, not chopped out, N.87°W., 30.4 ft.  
1894 BT, S.34°E., 11.2 ft., now 14" dead snag, face open, scribes X chopped in bark.  
6" Alder BT, S.38°22'E., 35.62 ft., dying, with Weyer. Alum. tag.  
Set 5/8" Rod, 4.0 ft. tall, adjacent to rock and marked; 4 ft, dead Fir S.89°35'E., 4.6 ft., old "X" chopped in bark, placed Weyer. metal tag.  
Corner is located 92.86, slope dist. (81.09 horiz.) North of top of spur ridge which slopes Eastward towards Radar Creek, approx. ¼ mile Eastward down spur ridge from BLM, blacktopped Buck Mt. Road.

Tony Hostetter - For: Weyerhaeuser Co - 8/2007 - C.S.65/60-34

-----  
Found - No evidence of 5/8" rods set by Prahar  
14" snag, OBT, scribing visible, GLO rec. S.34°E., 11.2 ft.  
Set - 5/8"x36" rebar w/plastic cap mkd: "HOSTETTER LS 1075" at GLO bearing & dist. from the 14" snag described above, from which  
48" Fir stump, Prahar BT, no marks, bears East 6.0 ft. to center.  
12" Hemlock, scribed "S4 ¼ BT", bears S.16°E., 23.9 ft. to 6" spike.  
14" Fir, scribed "S ¼ BT" bears S.80°W., 32.7 ft. to 6" spike.  
12" Fir, unrecorded BT, WEYCO tag (reads: S.8°E., 14.5 ft.) N.8°W., 14.2 ft. to 6" spike (new)

Fd. IR & 5 BTs - 5/2008, by Ron Rice M156-12

continued next page

TOWNSHIP 23 RANGE 08 POINT IDENTIFIER # 338100

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. for Sec. 4, T24-8

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Stephan Stys - Crew: Brandon Campbell & John Rondeau -  
11/27/2022 - C.S. File 65/111-33

- 
- Found - A 5/8" iron rod w/ yellow plastic cap marked  
"HOSTETTER LS 1075" Set per CS 65/60-34.  
A 48" rotten fir stump bears N.90°E., 6.0'  
(S.89°35'E., 4.6' per CS 65/60-34).  
An 18" D.Fir w/visible scribe in face and tag bears  
S.16°E., 23.9' (per CS 65/60-34).  
A 19" uprooted D.Fir w/ healed face and tag bears  
S.80°W., 32.7' (per CS 65/60-34).  
A 17" D.Fir w/ healed face and tag bears N.8°W.,  
14.2' (per CS 65/60-34).  
A galvanized post bears S.60°E., 1.0' (unknown  
record).
- New - A 12" D.Fir, faced & scribed "N¼ S4 BT" with X-chop  
and tag bears S.74°W., 17.2' to a spike at side  
center.
- Note - Lat. and long. per GARMIN ETREX handheld GPS (and  
does not produce survey grade coordinates. 0  
N: 43°31'09.9" W: 123°39'17.3"  
Compass declination: 18° East.