

TOWNSHIP 23 RANGE 08 POINT IDENTIFIER # 340200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 28 and 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 6 Page(s) 2587)

Set a sandstone 14 x 10 x 5 ins., 10" in the ground for ¼ sec. cor. mkd. ¼ on W. face, from which
A Hemlock 10" dia., bears N.19°E., 6 lks. dist. mkd. ¼ S BT.
A Cedar 30" dia., bears S.73°E., 13 lks. dist. mkd. ¼ S BT

BLM resurvey by John A. Farmer, Cadastral Surveyor, under Group #1336, Surveyed Aug/Oct. 1986 - (DCSO records Vol. 48 Page(s) 18290)

The ¼ sec. cor., monumented with the original sandstone, 16 x 13 x 7 ins., (Rec. 14x10x5 ins.) firmly set 4" in the ground mkd. ¼ on S. face, from which the remains of the original bearing trees:

A Hemlock 21" dia., bears N.19°E., 7½ lks. dist. with healed blaze. (Rec. 6 lks.)
A root hole bears S.73°E., 13 lks. dist. with a down Cedar alongside, 30" dia., no marks visible.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 23 S R 8 W
¼ $\frac{S\ 28}{S\ 33}$
1986

from which a new bearing tree

A Cedar 48" dia., bears S.41°E., 26½ lks. dist. mkd. ¼ S33 BT.

From this point, United States Coast and Geodetic Survey triangulation station "OLD BLUE" bears S.24°13'30"W., 135.685 chs. dist., monumented with a standard brass tablet, 3½" dia., cemented in iron pipe 4" dia., firmly set, projecting 8" above ground, with top mkd. OLD BLUE 1953 and a triangle.