

TOWNSHIP 23 RANGE 08 POINT IDENTIFIER # 340300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 21 and 28

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 6 Page(s) 2589)

-----  
Set post 3 ft. long, 3" sq., 2 ft. in ground for ¼ sec. cor. marked ¼ S on N. face, from which  
A Cedar 30" dia., bears S.55°E., 9 lks. dist. mkd. ¼ S BT  
A Fir 40" dia., bears N.79°E., 27 lks. dist. mkd. ¼ S BT.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Dec. 1966 - C.S. File 54/12-47

-----  
Found - Orig. 30" now 38" Cedar S.55°W., 5.9 ft. (Not S.55°E.), now badly burned and hollow. No scribe found.

No trace of any tree as described to SE.  
Orig. 40" now 45" Fir snag, 30 ft. high, N.79°E., 17.8 ft. Open and find "¼S" scribe and reverse.

Set Brass cap at cor. mkd: County Surveyors Office

T 23 S R 8 W

¼ S 21  
S 28

1966

New BTs- 11" Hemlock N.42°W., 20.6 ft. mkd. ¼ S21 CS BT.

11" Hemlock S.70°E., 38.2 ft. mkd. ¼ S28 CS BT. This tree is most southerly, two Hemlocks joined at base.

This corner lies approx. 50 ft. West of spur, sloping NE.

Fd. and used in BLM resurvey by John A. Farmer, Cadastral Surveyor, under Group #1336, Surveyed Aug/Oct. 1986 - (DCSO records Vol. 48 Page(s) 18289)