

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 16 and 21

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 6 Page(s) 2591)

Set a sandstone 16x12x10 ins., 12" in ground mkd. ¼ on N. face, from which
A Fir 16" dia., bears S.38°W., 19 lks. dist. mkd. ¼ S BT
A Fir 30" dia., bears N.73°E., 141 lks. dist. mkd. ¼ S BT

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Feb. 1967 - C.S. File 54/12-31

Found - 4" x 4" squared post set in mound of broken sandstone, possible original corner stone.
Orig. 30" now 40" Fir N.73°E., 93.1 ft., turned out, open and find "S" scribe and reverse.
Orig. 16"(?) now approx. 70" Fir, S.38°W., 12.5 ft., now burned remains of stump, find old axe mark and possible scribe mark on burned blaze.

Set 1" IP & Brass cap at cor. mkd: County Surveyors Office
T 23 S R 8 W
¼ S 16
S 21
1967

Set in mound of stone & mark.
New BTs- 10" D.Fir N.77°E., 50.6 ft. mkd. ¼ S16 CS BT.
12" W.Fir S.16°W., 51.4 ft. mkd. ¼ S21 CS BT.
Marked "+ BO" on sandstone boulder 15'x14'x10 high.
Bearing S.80°W., 3.9 ft. to "+" 5 ft. above ground on overhang.

This corner lies moderate SE. slope in area of numerous small bluffs.

NOTE this corner was retyped from orig. corner report, there were various errors and omissions found. 11/8/2010, JC DCSO

Ronald L. Rice, Ward NW - Sept 2010 - C.S. File 65/69-53

Found - 2½" Douglas County brass cap dated 1967, with the following accessories:
Record 40" D.Fir down out of position
Rotted & burned (record 70") D.Fir stump bears S.38°W., 12.5' - no marks
Record + BO sloughed off - not found
15" D.Fir stump bears N.77°E., 50.6' - healed face
30" W.Fir bears S.74°E., 20.2' - healed face
(appears to be BLM BT by 1975 tag)

TOWNSHIP 23 RANGE 08 POINT IDENTIFIER # 340400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 16 and 21

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

New -	24" W. Fir bears S 16° W 51.4' - healed face (appears to be Douglas County BT by 1967 tag)
	13" D.Fir bears S.31°W., 29.2' - blazed, scribed "¼ S21 BT"
	8" D.Fir bears N.56°E., 15.7' - blazed, scribed "¼ S16 BT"
Note -	Corner has steel post adjacent to it. All BTs have red painted bands and yellow tags. Compass decl. 16°E.