

TOWNSHIP 23 RANGE 08 POINT IDENTIFIER # 340500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 9 and 16

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 6 Page(s) 2593-94)

Set a post 3 ft. long, 3" sq., 2 ft. in the ground for ¼ sec. cor. marked ¼ S on N. face, from which
A Fir 6" dia., bears N.3°W., 27 lks. dist. mkd. ¼ S BT.
A Fir 10" dia., bears S.31°E., 39 lks. dist. mkd. ¼ S BT.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Dec. 1966 - C.S. File 54/12-41

Found - Orig. 10" now 28" Fir, alive, S.31°E., 25.7 ft., previously opened and shows "¼S" scribe on decaying face.
Orig. 6" now 18" Fir snag with approx. 6 ft. of lower part buried in old slide, N.3°E., 17.8 ft.
Set Brass cap at cor. mkd: County Surveyors Office
T 23 S R 8 W
¼ $\frac{S \ 9}{S \ 16}$
1966
New BTs- 14" Hemlock N.67½°W., 58.9 ft. mkd. ¼ S9 CS BT.
32" D.Fir S.58°E., 16.4 ft. mkd. ¼ S16 CS BT.
Corner in bottom of ravine approx. 225 ft. East of top of ridge, course NE.

Ronald L. Rice, Ward NW - Feb. 18, 2009 - C.S. File 65/66-11

Found - 2½" Douglas County brass cap dated 1966 with the following accessories:
40" D.Fir bears S.31°W., 25.7' healed face
28" Hemlock bears N.67½°W 58.9 healed face
43" D.Fir bears S.58°E., 16.4 healed face
Unrecorded 25" D.Fir bears N.26°W. 29.0' healed face
Note - Corner has steel post adjacent to it. All BTs have red painted bands and yellow tags.
16° East.