

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 27 and 28

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 6 Page(s) 2577)

-----  
Set post 3 ft. long, 3" sq., 2 ft. in ground for ¼ sec. cor. mkd. ¼ S on W. face, from which  
A Fir 50" dia., bears West, 4 lks. dist. mkd. ¼ S BT.  
A Fir 50" dia., bears S.66°E., 18 lks. dist. mkd. ¼ S BT

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Dec. 1966 - C.S. File 54/12-50

-----  
Found - Very old squared post, badly rotted.  
Orig. 50" now 50" Fir, S.66°E., 11.9 ft., shows old bark scribed "¼" and fragmentary scribe marks, alive.  
Orig. 50" now 56" Fir, West 2.6 ft., shows "¼S BT" bark scribe in poor condition, alive.

Set Brass cap at cor. mkd: County Surveyors Office  
T 23 S R 8 W  
¼ S28|S27  
1966

Brass cap set at base of original BT to West.  
New BTs- 5" Hemlock S.59°E., 7.2 ft. mkd. ¼ S27 CS BT.  
6" Hemlock S.30°W., 13.2 ft. mkd. ¼ S28 CS BT.  
Corner lies on NE. slope in heavy timber approx. 150 ft. North of road, course SW. and NE.

Fd. OK, March 1982 by L. Roberts - M 92-3

BLM resurvey by John A. Farmer, Cadastral Surveyor, under Group #1336, Surveyed Aug/Oct. 1986 - (DCSO records Vol. 48 Page(s) 18285-86)

-----  
The ¼ sec. cor., perpetuated and recorded by Tracy in 1966, monumented with an iron pipe 1½" dia., firmly set, projecting 4" above ground with brass cap mkd. in 1966 from which the remains of the original bearing trees:

A Fir stump 40" dia., bears S.66°E., 18 lks. dist., no marks visible.

A Fir stump 54" dia., bears West, 4 lks. dist., no marks visible.

and remains of bearing trees mkd. by Tracy:

A Hemlock stump 6" dia., bears S.59°E., 11 lks. dist. with healed blaze.

A Hemlock 9" dia., bears S.30°W., 20 lks. dist. with healed blaze.

(Cont. Next Page)

TOWNSHIP 23 RANGE 08 POINT IDENTIFIER # 400240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 27 and 28

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and a new bearing tree:

A Hemlock 12" dia., bears S.30 3/4°E., 91 lks. dist. mkd.  
¼ S27 BT.