

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 6 Page(s) 2578)

-----  
This point falling on solid bed rock, I made a cross (X) at the exact corner point with 2 notches S. and 3 notches E. from corner point, from which  
A Hemlock 24" dia., bears N.22°E., 87 lks. dist. mkd. T23S R8W S22 BT.  
A Fir 50" dia., bears S.81½°E., 205 lks. dist. mkd. T23S R8W S27 BT.  
A Fir 12" dia., bears S.11°W., 100 lks. dist. mkd. T23S R8W S28 BT.  
A Fir 30" dia., bears N.20°W., 124 lks. dist. mkd. T23S R8W S21 BT.

Douglas Co. Surveyors Office - Gary L. Langlitz, Deputy, P. Earle, crew - May 15, 1974 - C.S. File 56/51-10

-----  
Found - Small (X) chiseled in sandstone bedrock, could not find notches called for in orig. notes, from which  
Orig. 12" now approx. 26" rotten Fir stob with faint bark scribe "BT" at base bears at record bearing and distance S.11°W., 66.0 ft.  
A 60" D.Fir apparently thought to have been an OBT bears S.81½°E., 132.7 ft. (Rec.S.81½°E., 135.3 ft.) This tree has been opened previously, we find no markings.

No trace of orig. NE. and NW. bearing tree.  
Set Brass cap in a drill hole in rock at cor. mkd:

County Surveyors Office  
T 23 S R 8 W  
S 21 | S 22  
S 28 | S 27  
1974

New BTs- A 12" D.Fir bears S.17°E., 26.9 ft. scribed "T23S R8W S27 CS BT".  
12" D.Fir bears N.20°E., 34.5 ft. scribed "T23S R8W S22 CS BT".  
14" D.Fir bears N.68½°W., 21.7 ft. scribed "T23S R8W S21 CS BT"  
15" D.Fir bears S.70°W., 34.6 ft. scribed "T23S R8W S28 CS BT"

Corner is set on an exposed sloping sandstone face in the bottom of a small ravine on a steep north-easterly slope, ravine course N.40°E.

TOWNSHIP 23 RANGE 08 POINT IDENTIFIER # 400300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 21, 22, 27, and 28

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM resurvey by John A. Farmer, Cadastral Surveyor, under Group #1336, Surveyed Aug/Oct. 1986 - (DCSO records Vol. 48 Page(s) 18286-87)

-----  
The Sec. cor., perpetuated and recorded by Langlitz in 1974, from original evidence no longer in existence, monumented with a brass disc, 3p" dia., firmly set in a drill hole in solid rock, with top mkd. as in 1974  
from which the remains of bearing trees mkd. by Langlitz:  
A Fir stump 12" dia. bears S.69°W., 52 lks with healed blaze  
A Fir 17" dia., bears N.69°W., 33 lks., with healed blaze.  
and a new bearing tree:  
A Fir 15" dia., bears S.64¾°E., 61 lks. mkd. T23S R8W S27 BT  
No other suitable trees available.

BLM dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2781, surveyed May/Aug. 2015 - (DCSO records Vol. 58 Page(s) 23411)

-----  
The cor. of secs. 21, 22, 27, and 28, monumented with a brass tablet, 3¾" dia., firmly set, with top flush with the surface of solid rock, with top (brass cap properly) mkd.  
from which the remains of the bearing trees mkd. by Langlitz, in 1974 and reported by Farmer  
A fir high stump, 15" dia., bears S.69°W., 34.3 ft., with a healed blaze.  
A fir, 21" dia., bears N.69°W., 21.8 ft., with a healed double blaze.  
and a bearing tree mkd. by Farmer in 1986  
A fir, 18" dia., bears S.64¾°E., 40.3 ft., with a healed blaze.  
and new bearing trees  
A fir, 10" dia., bears N.22¾°E., 41.2 ft., mkd. T23S R8W S21 BT.  
A fir, 6" dia., bears S.76°W., 27.0 ft., mkd. X BT.  
Drive an aluminum angle iron 4½ ft. northerly of the cor.  
Corner is located on steep bare rock face, 50 ft. wide, slopes NE.  
Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center and has a magnet deposited in a white plastic case at the base of the stainless steel post. Alum. angle irons were driven alongside each corner unless an existing guard post was noted in the corner description.

NAD 1983 (2011)  
Latitude: 43°32'53.996"N. Longitude: 123°38'39.152"W.