

PRIMARY CORNER DESCRIPTION Sec. Cor. for 15, 16, 21 and 22

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 6 Page(s) 2579-80)

 Set post 4 ft. long, 4" sq., 2 ft. in ground for cor. to secs. 15, 16, 21 and 22 mkd. T23S S15 on NE.; R8W S22 on SE.; S21 on SW.; and S16 on NW. faces with 3 notches on S. and E. edges, from which
 A Fir 28" dia., bears N.35°E., 7 lks. mkd. T23S R8W S15 BT
 A Fir 40" dia., bears S.66°E., 19 lks. mkd T23S R8W S22 BT
 A Fir 24" dia., bears S.51°W., 16 lks. mkd T23S R8W S21 BT
 A Fir 8" dia., bears N.77°W., 35 lks. mkd. T23S R8W S16 BT

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Feb. 1967 - C.S. File 54/12-32

 Found - Orig. 28" now 34" Fir snag, N.35°E., 4.6 ft., shows "T2 S R8W S15 BT", bark scribe in poor condition.
 Orig. 40" now 44" Fir snag, S.66°E., 12.5 ft., shows scar. Do not open.
 Orig. 8" now 24" Fir, alive, N.77°W., 23.1 ft., shows faint scar. Rescribed "T23S R8W S16 CS BT"
 Large hole where SW. BT once stood.
 Set Brass cap at cor. mkd: County Surveyors Office
 T 23 S R 8 W
 S 16 | S 15
 S 21 | S 22
 1967
 New BTs- 10" D.Fir S.70°W., 16.7 ft. mkd. T23S R8W S21 CS BT
 6" D.Fir S.20°W., 19.3 ft. mkd. T23S R8W S21 CS BT
 5" W.Fir N.49°E., 22.8 ft. mkd. S15 CS BT.
 No suitable tree to SE.
 Corner lies on steep, South slope approx. 4 chains N. of Mehl Creek.

Fd. OK, May 1986 - I.P. Company Tags added - C.S. 63/37-1

BLM dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2781, surveyed May/Aug. 2015 - (DCSO records Vol. 58 Page(s) 23413)

 The cor. of secs. 15, 16, 21, and 22, perpetuated by the Douglas Co Surveyor's Office in 1967; monumented with an iron post, 1½" dia., firmly set, projecting 7" above ground, with a brass cap (properly) mkd.
 from which the remains of the original bearing trees
 A fir high stump, 35" dia., bears S.66°E., 12.5 ft., with illegible scribe marks visible on open blaze.
 continued next page

TOWNSHIP 23 RANGE 08 POINT IDENTIFIER # 400400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 15, 16, 21 and 22

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A decayed fir high stump, 15" dia., bears N.77°W., 22.2 ft., with a decayed healed blaze. (Record, 23.1 ft.) and the remains of a bearing tree mkd. by person(s) unknown, as reported by Roberts, PLS 1039, in January, 1981

A tin-capped fir stump, 19" dia., bears S.87°W., 7.3 ft., with no marks visible on open decayed blaze.

and new bearing trees

A fir, 7" dia., bears N.5°E., 11.0 ft., mkd. X BT.

A fir, 15" dia., bears S.76°E., 53.3 ft., mkd. T23S R8W S22 BT.

A fir, 12" dia., bears S.32°W., 14.5 ft., mkd. T23S R8W S21 BT.

A fir, 15" dia., bears N.80°W., 16.6 ft., mkd. T23S R8W S16 BT.

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center and has a magnet deposited in a white plastic case at the base of the stainless steel post. Alum. angle irons were driven alongside each corner unless an existing guard post was noted in the corner description.