

TOWNSHIP 23 RANGE 08 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 9, 10, 15 and 16

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCS0 records Vol. 6 Page(s) 2581-82)

Set post 4 ft. long, 4" sq., 2 ft. in ground for cor. to secs. 9, 10, 15 and 16, mkd. T23S S10 on SE.; R8W S15 on SE.; S16 on SW.; and S9 on NW. faces with 4 notches on S. and 3 notches on E. edges, from which

- A Fir 30" dia., bears N.25°E., 78 lks. dist. mkd. T23S R8W S10 BT.
- A Fir 24" dia., bears S.80°E., 23 lks. dist. mkd. T23S R8W S15 BT.
- A Fir 12" dia., bears S.20°W., 65 lks. dist. mkd. T23S R8W S16 BT.
- A Fir 36" dia., bears N.3°W., 64 lks. dist. mkd. T23S R8W S9 BT.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Feb/March 1967 - C.S. File 54/12-29

-
- Found - Orig. 30" now 40" Fir, alive, N.25°E., 51.5 ft., shows good scar. We rescribe "T23S R8W S10 CS BT"
- Orig. 24" now 36" Fir, alive, S.80°E., 15.2 ft., shows good scar. We rescribe "T23S R8W S15 CS BT"
- Orig. 12" now 30" Fir, alive, S.20°W., 42.9 ft., shows faint scar. We rescribe "T23S R8W S16 CS BT"
- Orig. 36" now 42" Fir, alive, N.3°W., 42.2 ft., alive, shows bark scribe. We rescribe "T23S R8W S9 CS BT"

(We used original BTs because no small trees in area)
Set Brass cap at cor. mkd: County Surveyors Office

T	23	S	R	8	W
	S	9		S	10
	S	16		S	15
				1967	

Corner lies on very steep, SE. slope, 200 ft. West of bottom of ravine.

David Edwards - 1/23/2025 - C.S. File 65/113-54

Found - 1967 DCS0 brass cap.
The 4 original BTs noted in the 1967 renewal are fd to be metal capped stumps in the positions noted in 1967.
continued next page

TOWNSHIP 23 RANGE 08 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 9, 10, 15 and 16

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

New - A 10" diam fir scribed "S10 BT" bears N.59°E. 11.7'
An 11" diam fir scribed "S15 BT" bears S.22°E. 18.4
5.5' steel posts are set 2' S. on line and 2' W.
Compass decl. 15°E.