

PRIMARY CORNER DESCRIPTION AP on No. bdy. Section 3

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1552)

Set standard cor. of secs. 3 and 4, from which
A Fir 30" dia., bears S.49°W., 180 lks. dist.
A Fir 18" dia., bears S.44°E., 225 lks. dist.

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 6 Page(s) 2585)

The cor. to secs. 3 and 4, at which point I set a post 4 ft. long, 4" sq., 24" in the ground for closing cor. to secs. 3 and 4 mkd. C C T23S R8W on S.; S3 on E.; and S4 on W., with 3 notches on E. and W. sides, from which
A Fir 24" dia., bears S.52½°E., 272 lks. dist. mkd. T23S R8W S3 BT.
A Fir 50" dia., bears S.31°W., 138 lks. dist. mkd. T23S R8W S4 BT.
No tree in limits N. of line. Pit impracticable.

BLM resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #640, surveyed July 1967/April 1968 (DCSO records Vol. 35 Page(s) 14428)

The standard cor. of secs. 3 and 4, determined at record bearing and distance from the original bearing trees
A sawed Fir stump 40" dia., bears S.44°E., 225 lks. dist. with fragmentary scribe marks visible on opened blaze. (this tree was also used as the SE BT for the closing cor. of secs. 3 and 4 established by Whipple in 1894)
A rotted Fir crown, size indeterminate, bears S.29°W., 180 lks. dist. no marks remaining. (This tree was also used as the SW. BT for the closing cor. of secs. 3 and 4 established by Whipple in 1894)

THIS CORNER NOW BECOMES AN ANGLE POINT ON LINE.

At the corner point
Set an iron post, 28" long, 2 1/2" dia., 25" in the ground, with brass cap mkd:
AP
S \ /3
T 23 S R 8 W
1967

from which
A W.Oak 12" dia., bears S.59°E., 183 lks. dist. mkd. AP S3 BT.
A W.Oak 18" dia., bears S.28°E., 228 lks. dist. mkd. AP S3 BT.