

TOWNSHIP 23 RANGE 08 POINT IDENTIFIER # 438100

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. for Sec. 3 only, T24-8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 6 Page(s) 2541)

Set a post 4 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. marked ¼ S on N. face, from which
A Fir 48" dia., bears S.59°W., 10 lks. dist. mkd. ¼ S BT
A Fir 18" dia., bears N.46°W., 39 lks. dist. mkd. ¼ S BT

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Feb. 1967 - C.S. File 54/12-16

Found - Orig. 48" now 56" Fir S.59°W., 6.6 ft., alive, shows good scars. We do not open.
Orig. 18" now 26" Fir, N.46°W., 25.7 ft., alive, open and find "4" scribe and reverse.

Set Brass cap at cor. mkd: County Surveyors Office

¼ $\begin{array}{c} \text{T } 23 \text{ S} \\ \text{S } 3 \text{ T } 24 \text{ S} \end{array}$ R 8 W
1967

New BTs- 5" D.Fir S.15½°W., 38.6 ft. mkd. ¼ S3 CS BT.

10" D.Fir S.20°E., 47.5 ft. mkd. ¼ S3 CS BT.

Corner lies on steep, southerly slope and 176.6 ft. W. of the ¼ corner of sec. 34 only.

Ron Quimby - For: Roseburg Resources Co. - 4/2018 - M174-23

Found - brass cap

17" Fir bears S.20°E., 47.5' - healed face

12" Fir bears S.15°30'W., 8.6' - healed face

61" Fir bears S.59°W., 6.6' - healed face

28"x6' tall fir stump bears N.46°W., 25.7' open face, scribe no longer visible

New BT - 12" fir bears S.57°E., 49.2' scribed "1/4 S3 BT"