

TOWNSHIP 23 RANGE 08 POINT IDENTIFIER # 440100

PRIMARY CORNER DESCRIPTION So. 1/4 cor. for Sec. 34 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 6 Page(s) 2554)

Set a post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. marked ¼ S on N. face, from which
A Laurel 12" dia., bears N.40°E., 12 lks. dist. mkd. ¼ S BT.
A Fir 30" dia., bears S.17°E., 47 lks. dist. mkd. ¼ S BT.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Feb. 1967 - C.S. File 54/12-15

Found - Orig. 30" now 40" Fir S.17°E., 31.0 ft., alive, shows good bark scribe "¼ S" and fragmentary "BT"
Orig. 12" now 15" Laurel N.40°E., 7.9 ft. open and find fragmentary reverse scribe. Alive.
In excavating to set new monument, we find sharpened end of very old Cedar post.
Set Brass cap at cor. mkd: County Surveyors Office
¼ S 34 T 23 S R8W
1967 T 24 S
New BTs- 6" D.Fir N.73°E., 24.3 ft. mkd. ¼ S34 CS BT.
24" Laurel N.37°W., 31.2 ft. mkd. ¼ S34 CS BT.
Corner lies 10 ft. W. of top of ridge, course SE. and 176.6 ft. E. of the ¼ cor. of sec. 3, T24S R8W.

Ron Quimby - For: Roseburg Resources Co. - 4/2018 - M174-23

Found - brass cap
15" Laurel bears N.40°E., 7.9' open scar (too rotten to read)
19" Fir bears N.73°E., 24.3' - healed face
49" Fir bears S.17°E., 31.0' partially visible scribe
29" laurel bears N.37°W., 31.2' healed face
New BT - 12" fir bears S.35°W., 10.8' scribed "1/4 S34 BT"