

TOWNSHIP 23 RANGE 08 POINT IDENTIFIER # 440200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 27 and 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 6 Page(s) 2577)

Set a post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. mkd. ¼ S on N. face, from which
A Cedar 12" dia., bears N.21°E., 72 lks. dist. mkd. ¼ S BT
A Cedar 30" dia., bears S.7°W., 57 lks. dist. mkd. ¼ S BT

Douglas Co. Surveyors Office - C.S. File 54/12-43A - Jan 1967

Corner searched for, not found.

Ron Quimby - For: Roseburg Resources Co. - 4/2018 - M174-23

Set - 5/8"x30" iron rod w/2" alum. Cap stamped
ROSEBURG RESOURCES COMPANY
S27
¼ o
S34
2018

New BTs- 8" Fir bears N.66°E., 15.7' scribed "¼ S27 BT"
14" Hemlock bears S.32°E., scribed "¼ S34 BT"
13" Hemlock bears S.84°W., scribed "¼ S34 BT"
10" Fir bears N.50°W., 19.9' scribed "¼ S27 BT"