

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 3 and 10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 6 Page(s) 2584)

Set a post 3 ft. long, 3" sq., 2 ft. in ground for ¼ sec. cor. mkd. ¼ S on North face, from which,
A Fir 48" dia., bears S.70°W., 35 lks. dist. mkd. ¼ S BT.
A Fir 10" dia., bears N.32°W., 32 lks. dist. mkd. ¼ S BT.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew May 8, 1967 - C.S. File 54/12-67

Found - Orig. 48" now 58" Fir, S.70°W., 23.1 ft., now down and slid downhill 3- ft. No scar showing, probably face down.
Orig. 10" now 30" Fir, N.32°W., 21.1 ft., alive, we chop open and find "B" scribe and reverse.
Set Brass cap at cor. mkd: County Surveyors Office
T 23 S R 8 W
¼ $\frac{S \ 3}{S \ 10}$
1967
New BTs- 7" Hemlock S.48°W., 35.1 ft. mkd. ¼ S10 CS BT.
8" Chinquapin N.59°E., 14.6 ft. mkd. ¼ S3 CS BT.
Corner lies on steep, southerly slope approx. 10 chs. East of top of main ridge, course NE-SW.

BLM resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #640, surveyed July 1967/April 1968 (DCSO records Vol. 35 Page(s) 14441)

The ¼ sec. cor., perpetuated and recorded by Tracy in 1967, monumented with an iron post 1½" dia., firmly set, projecting 10" above ground, with brass cap mkd. in 1967 from which the original bearing trees
A Fir 28" dia., bears N.32°W., 32 lks. dist., with fragmentary scribe mrks visible on opened blaze.
A root hole bears S.70°W., 35 lks. dist., alongside of which is a down Fir, 52" dia., with healed blaze.
and bearing trees mkd. by Tracy:
A Chinquapin 7" dia., bears N.60°E., 22 lks. dist. with scribe marks ¼ S3 CS BT visible on open double blaze.
A W.Fir 8" dia., bears S.47°W., 54 lks. dist. with scribe marks ¼ S10 CS BT visible on open double blaze.
Add marks BLM 1967 to brass cap.
Corner falls at bottom of descent, slopes S.

continued next page

TOWNSHIP 23 RANGE 08 POINT IDENTIFIER # 440600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 3 and 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2772, surveyed Sept./Nov. 2014 - (DCSO records Vol. 58 Page(s) 23274)

The ¼ sec. cor. of secs. 3 and 10, monumented with an iron post, 1½" dia., firmly set, projecting 7" above ground, with a brass cap (properly) mkd.

from which the remains of an original bearing tree

A tin-capped fir stump, 33" dia., bears N.32°W., 21.1 ft., with a healed blaze.

and new bearing trees

A fir, 15" dia., bears N.8°E., 31.4 ft., mkd. ¼ S3 BT.

A fir, 14" dia., bears S.57°W., 42.7 ft., mkd. ¼ S10 BT.