

TOWNSHIP 23 RANGE 08 POINT IDENTIFIER # 440700

PRIMARY CORNER DESCRIPTION Standard 1/4 Cor. Sec. 3 only, (North)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1552)

Set standard ¼ sec. post, from which
A Maple 5" dia., bears S.62°E., 31 lks. dist.
A Maple 10" dia., bears S.10°W., 51 lks. dist.

BLM resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #640, surveyed July 1967/April 1968 (DCSO records Vol. 35 Page(s) 14427)

(36.70 chs.)
Record distance for the standard ¼ sec. cor. of sec. 3 only, there is no remaining evidence of the original corner. This corner is superseded by the following corner based on the 1894 Whipple survey.

(36.82 chs.) (N.89°31'W.)
Point for the ¼ sec. cor. of sec. 3 only, at midpoint longitudinally on the N. bdy. of the section.
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

¼ S 3
T 23 S R 8 W
1967

from which
A W.Fir 13" dia., bears S.46°E., 28 lks. mkd. ¼ S3 BT.
A Fir 18" dia., bears S.41°W., 28 lks. mkd. ¼ S3 BT.

BLM Dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2772, surveyed Sept./Nov. 2014 - (DCSO records Vol. 58 Page(s) 23270)

The ¼ sec. cor. of sec. 3 only, monumented with an iron post, 2½" dia., firmly set, projecting 4" above ground, with a brass cap (properly) mkd.

from which the remains of the BTs mkd. by Peterson in 1967-68
A fir, 25" dia., bears S.46°E., 17.5 ft., with a healed blaze. (Record, white fir, 18.5 ft.)

A decayed fir stump, 13" dia., bears S.37°W., 17.6 ft., no marks visible. (Record, S.41°W., 18.5 ft.)
and a new bearing tree

A white fir, 16" dia., bears S.41½°W., 22.0 ft., mkd. ¼ S3 BT.