TOWNSHIP 23 RANGE 08 POINT IDENTIFIER # 500100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 34 & 35 only, (South)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 6 Page(s) 2553)

Set a post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 34 and 35, marked T23S R8W on N.; S35 on E.; and S34 on W. with 2 notches on E. and 4 notches on W. edges, from which
A Fir 8" dia., bears N.75°E., 31 lks. dist. mkd. T23S R8W S35 BT.
A Fir 30" dia., bears N.28°W., 38 lks. dist. mkd. T23S R8W S34 BT.
A Fir 60" dia., bears S.13°W., 61 lks. dist. mkd. T23S R8W S34 & 35 BT.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Feb. 1967 - C.S. File 54/12-17

Found - Orig. 8" now 12" Fir, N.75°E., 20.5 ft. Open and find "W S" scribe & reverse. Alive.
NW. and SW. BTs down, bark scribe visible on NW BT.
Set Brass cap at cor. mkd: County Surveyors Office
S 34 | S 35 T 23 S
1967 T 24 S R8W
New BTs- 12" D.Fir N.75°E., 20.5 ft. rescribed "T23S R8W S35 CS BT"
17" D.Fir N.63°W., 69.6 ft. mkd. T23S R8W S34 CS BT.
Corner lies approx. 66 ft. E. of spur ridge, course S. and approx. 182 ft. E. of corner of secs. 2 & 3, T24-8

Ron Quimby - For: Roseburg Resources Co. - 4/2018 - M174-23

Found - brass cap
12" fir bears N.75°E., 20.5' no longer standing
20" rotten stump bears N.63°W., 69.6' no visible scribe
New BTs- 27" Fir bears N.55°E., 4.4' - (no record) visible scar and "BT" painted on it
9" Fir bears N.76°W., 35.7'
10" Fir bears N.56°W., 16.1'
8" Fir bears N.11°W., 8.9'
All three scribed "T23S R8W S34 BT"

Fd ok 5/2019, R Quimby C.S. File 65/102-49