

PRIMARY CORNER DESCRIPTION Sec. Cor. for 14, 15, 22 and 23

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 6 Page(s) 2568)

Set a post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 14, 15, 22 and 23, mkd. T23S S14 on NE.; R8W S23 on SE.; S22 on SW.; and S15 on NW. faces with 3 notches on S. and 2 notches on E. edges, from which

A Fir 24" dia., bears N.5°E., 23 lks mkd. T23S R8W S14 BT.
A Fir 24" dia., bears S.20°E., 19 lks mkd. T23S R8W S23 BT
A Fir 24" dia., bears S.45°W., 50 lks mkd. T23S R8W S22 BT
A W.Fir 20" dia. bears N.6½°W., 60 lks mkd T23S R8W S15 BT

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Feb/March 1967 - C.S. File 54/12-24

Found - Orig. 24" now 48" Fir, alive, N.5°E., 15.2 ft., shows scar. Do not open.
Orig. 24" Fir, now only decayed remains, S.20°E., 12.5 ft. Find old axe mark and partially burned face with fragmentary scribe marks.
Orig. 24" Fir, now badly decayed stump, S.45°W., 33.0 ft.

Hole in ground where NW. BT would have been.
Set Brass cap at cor. mkd: County Surveyors Office

T	23	S	R	8	W	
		S	15		S	14
		S	22		S	23
						1967

New BTs- 17" W.Fir S.50°W., 24.1 ft. mkd. T23S R8W S22 CS BT
14" D.Fir S.43½°E., 24.0 ft. mkd. T23S R8W S23 CSBT
11" D.Fir N.41°E., 54.8 ft. mkd. T23S R8W S14 CS BT
15" W.Fir N.26°W., 40.2 ft. mkd. T23S R8W S15 CS BT
Corner lies on gentle S. slope.

BLM dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2781, surveyed May/Aug. 2015 - (DCSO records Vol. 58 Page(s) 23407-8)

The cor. of secs. 14, 15, 22, and 23, perpetuated by the Douglas County Surveyor's Office in 1967; monumented with an iron post, 1½" dia., firmly set, projecting 8" above ground, with a brass cap (properly) mkd.
from which the remains of an original bearing tree
A fir stump, 43" dia., bears N.5°E., 15.2 ft., with remains of a healed blaze.
and the remains of the BTs mkd. by the Douglas Co Surveyor's Office
continued next page

TOWNSHIP 23 RANGE 08 POINT IDENTIFIER # 500400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 14, 15, 22 and 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A decayed fir snag, 9" dia., bears N.40½°E., 54.0 ft., with remains of a healed blaze.

A fir, 21" dia., bears S.43½°E., 24.2 ft., with a healed blaze.

A decayed white fir stump, size indeterminate, bears S.50°W., 24.0 ft., no marks visible.

A decayed white fir stump, size indeterminate, bears N.27°W., 39.7 ft., no marks visible.

and new bearing trees

A hemlock, 14" dia., bears N.46°E., 10.2 ft., mkd. T23S R8W S14 BT.

A fir, 15" dia., bears S.20°W., 19.3 ft., mkd. T23S R8W S22 BT.

A hemlock, 12" dia., bears N.57°W., 7.7 ft., mkd. T23S R8W S15 BT.

An iron rod is alongside the cor.

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center and has a magnet deposited in a white plastic case at the base of the stainless steel post. Alum. angle irons were driven alongside each corner unless an existing guard post was noted in the corner description.