

PRIMARY CORNER DESCRIPTION East 1/4 Cor. for Sec. 3 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 6 Page(s) 2574)

Set a stone 14x12x6 ins., 10" in the ground for ¼ S. cor. mkd. ¼ on W. face, from which
A Fir 50" dia., bears S.64°E., 93 lks. dist. mkd. ¼ S BT
A Cedar 12" dia., bears S.2°W., 58 lks. dist. mkd. ¼ S BT

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Feb/March 1967 - C.S. File 54/12-59

Found - Orig. corner stone mkd. "¼" on W. face, fell apart on removal.
Orig. 50" now 55" Fir S.64°E., 61.4 ft., alive, shows "¼S" bark scribe in fair condition. Top of tree gone, approx. 100 ft. high.
Orig. 12" now 32" Cedar, alive, S.2°W., 38.3 ft., no scar. Rescribe "¼ S3 CS BT".

Set brass cap in place of rock, mkd: County Surveyors Office
T 23 S R 8 W
¼ S 3 | S 2
1967

New BT - 10" D.Fir S.28°E., 25.3 ft. mkd. ¼ S2 CS BT.
Corner lies on steep South slope 20 ft. N. of small creek, course S.70°E. Put pieces of corner stone in brass cap hole.

BLM resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #640, surveyed July 1967/April 1968 (DCSO records Vol. 35 Page(s) 14438)

The ¼ sec. cor. of sec. 3 only, perpetuated and recorded by Tracy in 1967, monumented with an iron post 1½" dia., firmly set, projecting 6" above ground with brass cap as mkd. by Tracy,

from which the original bearing trees:
A Fir 58" dia., bears S.64°E, 93 lks. dist., with scribe marks ¼ S visible on weathered bark blaze.
A Cedar 34" dia., bears S.2°W., 58 lks. dist. with healed blaze. Remarked by Tracy in 1967; scribe marks ¼ S3 CS BT visible on open double blaze.
and a bearing tree mkd. by Tracy:
A Fir 10" dia., bears S.28°E., 38 lks. dist., with scribe marks ¼ S2 CS BT visible on open double blaze.
Add marks BLM 1967 to brass cap.

(Cont. Next Page)

TOWNSHIP 23 RANGE 08 POINT IDENTIFIER # 500638

PRIMARY CORNER DESCRIPTION East 1/4 Cor. for Sec. 3 only

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Douglas Co. Surveyors Office - Gregory Quibell, Deputy - John Powell; Randy Smith, crew - Jan. 13, 1983 - C.S. File 62/7-2

Found - 1" I.P. with DCSO brass cap mkd. as shown in 1967.
Orig. 12" Cedar now 44" with good scar, bears S.2°W., 38.3 ft.
Orig. 50" Fir now 59" with bark scribed "¼S" visible, bears S.64°E., 60.7 ft.
10" Fir now 13" with good scar, bears S.29°E., 25.1 ft.

Since this corner is the ¼ corner to sec. 3 only, I "X" out the S2 which was stamped on the cap in 1967.
A newly blazed line runs North and South from corner.