

PRIMARY CORNER DESCRIPTION Standard Cor. secs. 2 & 3 only, (North)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1552)

-----  
Set standard cor. of secs. 2 and 3, from which  
A Maple 5" dia., bears S.68°E., 30 lks. dist.  
A Maple 6" dia., bears S.20°W., 17 lks. dist.

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 6 Page(s) 2575)

-----  
At the standard cor. to secs. 2 and 3. The old post being gone and the BTs greatly decayed, I reestablished this corner as follows vis: Set a sandstone 16 x 12 x 8 ins., 12" in the ground for cor. marked S C., with 2 notches on E. and 4 notches on W. edges, from which  
A Fir 20" dia., bears S.62½°E., 59 lks. dist. which I mark T23S R8W S2 BT.  
A Maple 14" dia., bears S.7°W., 52 lks. dist. which I mark T23S R8W S3 BT.  
A Fir 40" dia., bears N.80°W., 65 lks. dist. which I mark T23S R8W C S 2 & 3 BT.

BLM resurvey by Floyd A. Brooks and James E. Jelley, Cadastral Surveyors, under Group #'s 514 and 350, surveyed June 1963/March 1965 (DCSO records Vol. 33 Page(s) 13672-73)

-----  
The stan. cor. of secs. 2 and 3, determined at record distance from the bearing trees marked by Whipple in 1894, when he remonumented the original corner:  
A Fir 40" dia., bears S.32½°E., 59 lks. dist. with a healed blaze. (Rec. brg. S.62½°E.)  
A Maple 18" dia., bears S.3°W., 52 lks. dist. with a healed blaze. (Rec. brg. S.7°W.)  
A Fir 42" dia., bears N.80°W., 65 lks. dist. with a healed blaze.

At the corner point  
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

-----  
S 3 | S 2  
T 23 S R 8 W  
S C  
1964

continued next page

TOWNSHIP 23 RANGE 08 POINT IDENTIFIER # 500700

PRIMARY CORNER DESCRIPTION Standard Cor. secs. 2 & 3 only, (North)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2772, surveyed Sept./Nov. 2014 - (DCSO records Vol. 58 Page(s) 23269)

-----  
The standard cor. of secs. 2 and 3 only, monumented with an iron post, 2½" dia., firmly set, projecting 3" above ground, with a brass cap (properly) mkd.

from which the bearing trees mkd. by Whipple in 1894

A fir, 52" dia., bears S.25°E., 38.9 ft., with a healed blaze and axe marks B and T on either side of a tag. (Record, S.32½°E.)

A maple, 23" dia., bears S.7°W., 34.3 ft., no marks visible. (Record, S.3°W.)

A fir, 55" dia., bears N.80°W., 42.9 ft., with a healed blaze.

The geographic position in NAD 1983 (2011) of the following corners as determined by ties from temporary GPS control points, established utilizing dual frequency, carrier phase GPS receivers, and processed using the National Geodetic Survey's OPUS:

The standard corner of sections 2 and 3 only, on the north boundary of the township (Fifth Standard Parallel South):  
Latitude: 43°36'22.98"N      Longitude: 123°37'26.06"W