

PRIMARY CORNER DESCRIPTION AP on So. bdy. Sec. 2

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 6 Page(s) 2535)

Marked a Fir 24" dia., from which
A Fir 18" dia., bears N.40°W., 17 lks. dist.
A Fir 36" dia., bears S.35°E., 13 lks. dist.

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 6 Page(s) 2573)

The witness cor. which is a Fir 30" dia. mkd. S2 on N.; T23S R8W on E.; S11 on S.; and WC on W. sides, from which
A Fir 24" dia., bears N.40°W., 17 lks. dist., mkd. T23S R8W S2 WC BT.
No other bearing tree standing.

BLM resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #640, surveyed July 1967/April 1968 (DCSO records Vol. 35 Page(s) 14440)

Point for the witness point of secs. 2 and 11, determined by the method of broken boundaries; this witness point now becomes an angle point.

Set an iron post 28" long, 2½" dia., 26" in the ground with brass cap mkd:

T 23 S R 8 W
A P
 \S 2
 S 11
 1967

from which
A Fir 10" dia., bears North 56 lks. dist., mkd. AP S2 BT
A Fir 10" dia., bears S.67°W., 33 lks. dist. mkd. AP S11 BT.